

## APC Easy 3S uninterruptible power supply (UPS) Double-conversion (Online) 30 kVA 30000 W

Brand : APC Product code: E3SUPS30KH

**Product name:** Easy 3S

APC Easy 3S. UPS topology: Double-conversion (Online), Output power capacity: 30 kVA, Output power: 30000 W. Form factor: Tower, Product colour: White, Display type: LED. Compliance certificates: RoHS, Certification: CE, EAC, IEC 62040-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE, REACH. Width: 250 mm, Depth: 800 mm, Height: 770 mm. Package width: 400 mm, Package depth: 982 mm, Package height: 1015 mm





Features		Design	
UPS topology *	power capacity * 30 kVA power * 30000 W power * 90000 W peration voltage (min) * 304 V peration voltage (max) * 477 V pequency * 45/65 Hz poperation voltage (min) 380 V poperation voltage (max) 415 V prequency 50/60 Hz peration voltage (max) 415 V prequency 50/60 Hz	International Protection (IP) code	IP20
Output power capacity *		Operational conditions	
Output power *  Waveform *  Input operation voltage (min) *  Input operation voltage (max) *  Input frequency *  Output operation voltage (min)  Output operation voltage (max)		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -15 - 40 °C 0 - 95% 0 - 95% 0 - 984.4 m 0 - 14763.6 m
Output frequency		Certificates	
Maximum current Number of input phases Number of output phases Input power factor		Compliance certificates  Certification	RoHS CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE, REACH
Crest factor		Packaging content	
Output voltage Total Harmonic Distortion (THD)	3%	Quick installation guide	✓
Input current Total Harmonic Distortion (THD)	3%	Weight & dimensions	250 mm
Noise level	63 dB	Width Depth	800 mm
Design	_	Height Weight	770 mm 60 kg
Form factor * Product colour *	Tower White	Packaging data	
Display type	LED	Package width	400 mm

Packaging data			
Package depth	982 mm		
Package height	1015 mm		
Package weight	77 kg		
Logistics data			
Harmonized System (HS) code	85078000		
Other features			
Output voltage	400 V		





731304339564

0731304339564

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.