



## APC Easy 3S uninterruptible power supply (UPS) Double-conversion (Online) 30 kVA 30000 W

Brand : APC

Product code: E3SUPS30KH

Product name : Easy 3S

APC Easy 3S. UPS topology: Double-conversion (Online), Output power capacity: 30 kVA, Output power: 30000 W. Form factor: Tower, Product colour: White, Display type: LED. Width: 250 mm, Depth: 800 mm, Height: 770 mm. Output voltage: 400 V



| Features                                       |                            | Design                             |                                                                                          |
|------------------------------------------------|----------------------------|------------------------------------|------------------------------------------------------------------------------------------|
| UPS topology *                                 | Double-conversion (Online) | International Protection (IP) code | IP20                                                                                     |
| Output power capacity *                        | 30 kVA                     | Certification                      | CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE, REACH |
| Output power *                                 | 30000 W                    |                                    |                                                                                          |
| Waveform *                                     | Pure sine                  | <b>Operational conditions</b>      |                                                                                          |
| Input operation voltage (min) *                | 304 V                      | Operating temperature (T-T)        | 0 - 40 °C                                                                                |
| Input operation voltage (max) *                | 477 V                      | Storage temperature (T-T)          | -15 - 40 °C                                                                              |
| Input frequency *                              | 45/65 Hz                   | Operating relative humidity (H-H)  | 0 - 95%                                                                                  |
| Output operation voltage (min)                 | 380 V                      | Storage relative humidity (H-H)    | 0 - 95%                                                                                  |
| Output operation voltage (max)                 | 415 V                      | Operating altitude                 | 0 - 984.4 m                                                                              |
| Output frequency                               | 50/60 Hz                   | Non-operating altitude             | 0 - 14763.6 m                                                                            |
| Maximum current                                | 55 A                       | <b>Technical details</b>           |                                                                                          |
| Number of input phases                         | 3                          | Compliance certificates            | RoHS                                                                                     |
| Number of output phases                        | 3                          | <b>Weight &amp; dimensions</b>     |                                                                                          |
| Input power factor                             | 0.99                       | Width                              | 250 mm                                                                                   |
| Crest factor                                   | 3:1                        | Depth                              | 800 mm                                                                                   |
| Output voltage Total Harmonic Distortion (THD) | 3%                         | Height                             | 770 mm                                                                                   |
| Input current Total Harmonic Distortion (THD)  | 3%                         | Weight                             | 60 kg                                                                                    |
| Noise level                                    | 63 dB                      | Package width                      | 400 mm                                                                                   |
| <b>Design</b>                                  |                            | Package depth                      | 982 mm                                                                                   |
| Form factor *                                  | Tower                      | Package height                     | 1015 mm                                                                                  |
| Product colour *                               | White                      | Package weight                     | 77 kg                                                                                    |
| Display type                                   | LED                        |                                    |                                                                                          |

**Packaging data**

Quick installation guide ✓

**Logistics data**


Harmonized System (HS) code 85078000

**Other features**

Output voltage 400 V



0731304339564



731304339564

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.