

## APC Easy 3S UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 30 kVA 30000 W

Tuotemerkki : APC

Tuotekoodi: E3SUPS30KH

Tuotteen nimi : Easy 3S


APC Easy 3S. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 30 kVA, Lähtöteho: 30000 W. Kotelo: Tower, Tuotteen väri: Valkoinen, Näytön tyyppi: LED. Vaatimustenmukaisuustodistukset: RoHS, Sertifiointi: CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE, REACH. Tuotteen leveys: 250 mm, Tuotteen syvyys: 800 mm, Tuotteen korkeus: 770 mm. Pakkauksen leveys: 400 mm, Pakkauksen syvyys: 982 mm, Pakkauksen korkeus: 1015 mm





Features		Design	
UPS topology *	Double-conversion (Online)	International Protection (IP) code	IP20
Output power capacity *	30 kVA	Operational conditions	
Output power *30000 WWaveform *Pure sineInput operation voltage (min) *304 VInput operation voltage (max) *477 VInput frequency *45/65 HzOutput operation voltage (min)380 V	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -15 - 40 °C 0 - 95% 0 - 95% 0 - 984.4 m 0 - 14763.6 m	
Output operation voltage (max) Output frequency	ency 50/60 Hz rrent 55 A put phases 3 utput phases 3	Certificates	
Maximum current Number of input phases Number of output phases		Compliance certificates Certification	RoHS CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE, REACH
Input power factor Crest factor	0.99 3:1	Packaging content	
Output voltage Total Harmonic Distortion (THD)	3%	Quick installation guide	1
Input current Total Harmonic Distortion (THD) Noise level	3% 63 dB	Weight & dimensions Width	250 mm
	63 GB	Depth	800 mm
Design		Height Weight	770 mm 60 kg
Form factor *	Tower		60 Kg
Product colour *	White	Packaging data	
Display type	LED	Package width	400 mm

Packaging data				
Package depth	982 mm			
Package height	1015 mm			
Package weight	77 kg			
Logistics data				
Harmonized System (HS) code	85078000			
Other features				
Output voltage	400 V			





731304339564

0731304339564

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.