



APC Easy 3S UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 40 kVA 40000 W

Tuotemerkki : APC

Tuotekoodi: E3SUPS40KH

Tuotteen nimi : Easy 3S

APC Easy 3S. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 40 kVA, Lähtöteho: 40000 W. Kotelo: Tower, Tuotteen väri: Valkoinen, International Protection (IP)-koodi: IP20. Vaatimustenmukaisuustodistukset: RoHS, Sertifiointi: CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE, REACH. Tuotteen leveys: 250 mm, Tuotteen syvyys: 900 mm, Tuotteen korkeus: 770 mm. Pakkauksen leveys: 400 mm, Pakkauksen syvyys: 1050 mm, Pakkauksen korkeus: 1015 mm



Features		Design	
UPS topology *	Double-conversion (Online)	International Protection (IP) code	IP20
Output power capacity *	40 kVA	Operational conditions	
Output power *	40000 W	Operating temperature (T-T)	0 - 40 °C
Waveform *	Pure sine	Storage temperature (T-T)	-15 - 40 °C
Input operation voltage (min) *	304 V	Operating relative humidity (H-H)	0 - 95%
Input operation voltage (max) *	477 V	Storage relative humidity (H-H)	0 - 95%
Input frequency *	45/65 Hz	Operating altitude	0 - 984.3 m
Output operation voltage (min)	380 V	Non-operating altitude	0 - 14763.6 m
Output operation voltage (max)	415 V	Certificates	
Output frequency	50/60 Hz	Compliance certificates	RoHS
Maximum current	73 A	Certification	CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE, REACH
Number of input phases	3	Packaging content	
Number of output phases	3	Quick installation guide	✓
Input power factor	0.99	Weight & dimensions	
Crest factor	3:1	Width	250 mm
Overload capacity (10 minutes)	125%	Depth	900 mm
Overload capacity (1 minute)	150%	Height	770 mm
Output voltage Total Harmonic Distortion (THD)	3%	Weight	70 kg
Input current Total Harmonic Distortion (THD)	3%	Packaging data	
Noise level	63 dB	Package width	400 mm
Design			
Form factor *	Tower		

Design		Packaging data	
Product colour *	White	Package depth	1050 mm
		Package height	1015 mm
		Package weight	86 kg
		Logistics data	
		Harmonized System (HS) code	85078000
		Other features	
		Output voltage	400 V



0731304339571



731304339571

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 21-MAR-2025. Prints or copies of Information are only valid on the printed Publication date