

APC Easy 3S uninterruptible power supply (UPS) Double-conversion (Online) 15 kVA 15000 W

Brand : APC Product code: E3SUPS15KHB2

Product name: Easy 3S


APC Easy 3S. UPS topology: Double-conversion (Online), Output power capacity: 15 kVA, Output power: 15000 W. Battery technology: Sealed Lead Acid (VRLA), Battery voltage: 240 V. Form factor: Tower, Product colour: White, Display type: LED. Width: 380 mm, Depth: 928 mm, Height: 1400 mm. Output voltage: 400 V





Features		Design	
UPS topology * Double-conversion (Online) Output power capacity * 15 kVA Output power * 15000 W Waveform * Pure sine	Display type International Protection (IP) code Certification	LED IP20 CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE, REACH	
Input operation voltage (min) * Input operation voltage (max) *	304 V 477 V	Operational conditions	
Input frequency * Output operation voltage (min) Output operation voltage (max) Output frequency Maximum current Number of input phases	put frequency * 45/65 Hz put operation voltage (min) 380 V put operation voltage (max) 415 V put frequency 50/60 Hz imum current 28 A	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -15 - 40 °C 0 - 95% 0 - 95% 0 - 999.9 m 0 - 15000 m
Number of output phases	3	Technical details	- 15000 III
Input power factor Output voltage Total Harmonic Distortion (THD)	0.99 3%	Compliance certificates Weight & dimensions	RoHS
Input current Total Harmonic Distortion (THD) Noise level	3% 60 dB	Width Depth Height	380 mm 928 mm 1400 mm
Battery		Weight	436 kg
Battery technology Battery voltage Number of batteries supported	Sealed Lead Acid (VRLA) 240 V 3	Package width Package depth Package height	563 mm 1014 mm 1640 mm
Design		Package weight	481 kg
Form factor *	Tower	Packaging data	
Product colour *	White	Quick installation guide	✓

Logistics data	
Harmonized System (HS) code	85078000
Other features	
Output voltage	400 V





731304428206

0731304428206



8592978120009

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.