




APC Easy 3S uninterruptible power supply (UPS) Double-conversion (Online) 20 kVA 20000 W

Brand : APC

Product code: E3SUPS20KHB2


Product name : Easy 3S

APC Easy 3S. UPS topology: Double-conversion (Online), Output power capacity: 20 kVA, Output power: 20000 W. Battery technology: Sealed Lead Acid (VRLA), Battery voltage: 240 V, Typical backup time at full load: 30 min. Form factor: Tower, Product colour: White, Display type: LED. Width: 380 mm, Depth: 928 mm, Height: 1400 mm. Output voltage: 400 V



Features		Design	
UPS topology *	Double-conversion (Online)	Product colour *	White
Output power capacity *	20 kVA	Display type	LED
Output power *	20000 W	International Protection (IP) code	IP20
Waveform *	Pure sine	Certification	CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE
Input operation voltage (min) *	304 V	Operational conditions	
Input operation voltage (max) *	477 V	Operating temperature (T-T)	0 - 40 °C
Input frequency *	45/65 Hz	Storage temperature (T-T)	-15 - 40 °C
Output operation voltage (min)	380 V	Operating relative humidity (H-H)	0 - 95%
Output operation voltage (max)	415 V	Storage relative humidity (H-H)	0 - 95%
Output frequency	50/60 Hz	Operating altitude	0 - 999.9 m
Maximum current	37 A	Non-operating altitude	0 - 15000 m
Number of input phases	3	Technical details	
Number of output phases	3	Compliance certificates	RoHS
Input power factor	0.99	Weight & dimensions	
Output voltage Total Harmonic Distortion (THD)	3%	Width	380 mm
Input current Total Harmonic Distortion (THD)	3%	Depth	928 mm
Noise level	60 dB	Height	1400 mm
Battery		Weight	446 kg
Battery technology	Sealed Lead Acid (VRLA)	Package width	563 mm
Battery voltage	240 V	Package depth	1014 mm
Number of batteries supported	3	Package height	1640 mm
Typical backup time at full load	30 min		

Design		Weight & dimensions	
Form factor *	Tower	Package weight	494 kg
		Packaging data	
		Quick installation guide	✓
		Logistics data	
		Harmonized System (HS) code	85078000
		Other features	
		Output voltage	400 V



0731304428244



731304428244



8592978121204

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.