



APC Easy 3S uninterruptible power supply (UPS) Double-conversion (Online) 30 kVA 30000 W

Brand : APC

Product code: E3SUPS30KHB

Product name : Easy 3S

Easy UPS 3S 30 kVA 400 V 3:3 UPS for internal batteries

APC Easy 3S uninterruptible power supply (UPS) Double-conversion (Online) 30 kVA 30000 W:

Easy UPS 3S 30 kVA 400 V 3:3 UPS for internal batteries

High-efficiency 3-phase UPS that features advanced product features, competitive specifications, and robust electrical design, making business continuity easy in the data center or electrical room. This is an exceptionally easy to install, operate, maintain, and service 30 kVA UPS, ideal for small and medium businesses. Includes dust filter and conformance-coated boards for harsh environments. This UPS is for internal batteries, but is supplied without batteries, so you can easily customize the battery runtime. For battery runtime details, see the runtime charts published under the Documents tab.



Features		Design	
UPS topology *	Double-conversion (Online)	Form factor *	Tower
Output power capacity *	30 kVA	Cooling type	Active
Output power *	30000 W	Product colour *	White
Input operation voltage (min) *	304 V	LED indicators	✓
Input operation voltage (max) *	477 V	International Protection (IP) code	IP20
Input frequency *	45/65 Hz	Operational conditions	
Output operation voltage (min)	380 V	Operating temperature (T-T)	0 - 40 °C
Output operation voltage (max)	415 V	Storage temperature (T-T)	-15 - 40 °C
Output frequency	50/60 Hz	Operating relative humidity (H-H)	0 - 95%
Maximum current	55 A	Storage relative humidity (H-H)	0 - 95%
Number of input phases	3	Operating altitude	0 - 999.9 m
Number of output phases	3	Non-operating altitude	0 - 15000 m
Efficiency	95%	Certificates	
Input power factor	0.99	Compliance certificates	RoHS
ECO mode	✓	Certification	CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE REACH
Emergency Power Off (EPO)	✓	Weight & dimensions	
Output voltage Total Harmonic Distortion (THD)	3%	Width	500 mm
Input current Total Harmonic Distortion (THD)	3%	Depth	969 mm
Noise level	63 dB	Height	1400 mm
Battery		Weight	152 kg
Battery technology	Sealed Lead Acid (VRLA)	Battery width	68.3 cm
Battery voltage	240 V	Battery depth	111.4 cm

Weight & dimensions	
Battery height	164 cm
Battery weight	190 kg
Logistics data	
Harmonized System (HS) code	85078000



0731304340812



731304340812

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.