

APC Easy 3S uninterruptible power supply (UPS) Double-conversion (Online) 30 kVA 30000 W

Brand : APC Product code: E3SUPS30KHB2

Product name: Easy 3S


APC Easy 3S. UPS topology: Double-conversion (Online), Output power capacity: 30 kVA, Output power: 30000 W. Battery technology: Sealed Lead Acid (VRLA), Battery voltage: 240 V, Typical backup time at full load: 25 min. Form factor: Tower, Product colour: White, Display type: LED. Compliance certificates: RoHS, Certification: CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE, REACH. Width: 500 mm, Depth: 969 mm, Weight: 584 kg





Features		Design	
UPS topology * Double-conversion (Online) Output power * 30 kVA Output power * 30000 W	30 kVA 30000 W	Product colour * Display type International Protection (IP) code	White LED IP20
Waveform * Input operation voltage (min) * Input operation voltage (max) * Input frequency * Output operation voltage (min) Output operation voltage (max) Output frequency Maximum current	ut operation voltage (min) * 304 V ut operation voltage (max) * 477 V ut frequency * 45/65 Hz tput operation voltage (min) 380 V tput operation voltage (max) 415 V tput frequency 50/60 Hz	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -15 - 40 °C 0 - 95% 0 - 9599 m 0 - 15000 m
Number of input phases	55 A 3	Certificates	
Number of output phases Input power factor Output voltage Total Harmonic Distortion (THD)	3 0.99 3%	Compliance certificates Certification	RoHS CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE, REACH
Input current Total Harmonic	3%	Packaging content	
Distortion (THD) Noise level	63 dB	Quick installation guide	✓
Battery		Weight & dimensions	
Battery technology Battery voltage Number of batteries supported Typical backup time at full load Sealed Lead Acid (VRLA) 4 25 min	Width Depth Weight	500 mm 969 mm 584 kg	
	25 min	Packaging data	
		Package width	683 mm

Design		Packaging data	
Form factor *	Tower	Package depth	1114 mm
		Package height	1640 mm
		Package weight	638 kg
		Logistics data	
		Harmonized System (HS) code	85078000
		Other features	
		Output voltage	400 V





731304428282

0731304428282



8592978131609

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.