




## APC Easy 3S UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 40 kVA 40000 W

**Tuotemerkki :** APC

**Tuotekoodi:** E3SUPS40KHB2

**Tuotteen nimi :** Easy 3S

APC Easy 3S. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 40 kVA, Lähtöteho: 40000 W. Akkuteknologia: Sealed Lead Acid (VRLA), Akun jännite: 240 V. Kotelo: Tower, Tuotteen väri: Valkoinen, International Protection (IP)-koodi: IP20. Tuotteen leveys: 500 mm, Tuotteen syvyys: 969 mm, Tuotteen korkeus: 1400 mm. Ulostulojännite: 400 V



Features		Design	
UPS topology *	Double-conversion (Online)	Product colour *	White
Output power capacity *	40 kVA	International Protection (IP) code	IP20
Output power *	40000 W	Certification	CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE, REACH
Waveform *	Pure sine		
Input operation voltage (min) *	304 V	Operational conditions	
Input operation voltage (max) *	477 V	Operating temperature (T-T)	0 - 40 °C
Input frequency *	45/65 Hz	Storage temperature (T-T)	-15 - 40 °C
Output operation voltage (min)	380 V	Operating relative humidity (H-H)	0 - 95%
Output operation voltage (max)	415 V	Storage relative humidity (H-H)	0 - 95%
Output frequency	50/60 Hz	Operating altitude	0 - 999.9 m
Maximum current	73 A	Non-operating altitude	0 - 15000 m
Number of input phases	3	Technical details	
Number of output phases	3	Compliance certificates	RoHS
Input power factor	0.99	Weight & dimensions	
Output voltage Total Harmonic Distortion (THD)	3%	Width	500 mm
Input current Total Harmonic Distortion (THD)	3%	Depth	969 mm
Noise level	63 dB	Height	1400 mm
		Weight	590 kg
Battery		Package width	683 mm
Battery technology	Sealed Lead Acid (VRLA)	Package depth	1114 mm
Battery voltage	240 V	Package height	1640 mm
Number of batteries supported	4	Package weight	643 kg

**Design**

Form factor \* Tower

**Packaging data**

Quick installation guide ✓

**Logistics data**

Harmonized System (HS) code 85078000

**Other features**

Output voltage 400 V



0731304428305



731304428305



8592978343583

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.