



APC MGE Galaxy 5500 uninterruptible power supply (UPS) Double-conversion (Online) 80 kVA 72000 W

Brand : APC

Product code: G55TUPSU80HS

Product name : MGE Galaxy 5500

80kVA, 72 kW, 400V, 3-Phase, Hard Wire In, Hard Wire Out, LCD


APC MGE Galaxy 5500 uninterruptible power supply (UPS) Double-conversion (Online) 80 kVA 72000 W:

A versatile 3-phase UPS for facility, industrial and data center applications. Configurable system with a comprehensive range of accessories to meet your application demands.

APC MGE Galaxy 5500. UPS topology: Double-conversion (Online), Output power capacity: 80 kVA, Output power: 72000 W. AC outlet types: Terminal, Power plug: Terminal. Battery voltage: 432 V, Battery recharge time: 10 h. Form factor: Tower, Product colour: Black, Grey, Display type: LCD. Width: 712 mm, Depth: 850 mm, Height: 1900 mm



Features		Design	
UPS topology *	Double-conversion (Online)	Form factor *	Tower
Output power capacity *	80 kVA	Product colour *	Black, Grey
Output power *	72000 W	Display type	LCD
Waveform *	Sine	LED indicators	✓
Input operation voltage (min) *	250 V	International Protection (IP) code	IP20
Input operation voltage (max) *	470 V	Certification	CE, EN/IEC 62040-3, IEC 62040-1-2, IEC 62040-2, ISO 9001, TUV, VDE
Input frequency *	45/65 Hz	Operational conditions	
Output operation voltage (min)	380 V	Operating temperature (T-T)	0 - 40 °C
Output operation voltage (max)	415 V	Storage temperature (T-T)	-20 - 45 °C
Maximum current	116 A	Operating relative humidity (H-H)	0 - 95%
Number of input phases	3	Storage relative humidity (H-H)	0 - 95%
Number of output phases	3	Operating altitude	0 - 3600 m
Efficiency	93.4%	Non-operating altitude	0 - 9000 m
Crest factor	3:1	Weight & dimensions	
Output voltage Total Harmonic Distortion (THD)	1%	Width	712 mm
Input current Total Harmonic Distortion (THD)	3%	Depth	850 mm
Noise level	61.40 dB	Height	1900 mm
Power protection features	Overload	Weight	520 kg
Ports & interfaces		Package width	980 mm
AC outlet types	Terminal	Package depth	960 mm
Power plug	Terminal	Package height	2030 mm
Battery		Package weight	540 kg
Battery voltage	432 V	Other features	
Battery recharge time	10 h	Output connections	HardWire 4-wire (3PH + G)
		Input connection type	HardWire 4-wire (3PH + G), HardWire 4-wire (3PH + N)
		Nominal output voltage	400 V
		Nominal input voltage	400 V
		Communication options, slot	SmartSlot



0731304299868



731304299868

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.