



P1 P2



1 WHITE/ORANGE  
 2 ORANGE  
 3 WHITE/GREEN  
 6 GREEN  
 4 BLUE  
 5 WHITE/BLUE  
 7 WHITE/BROWN  
 8 BROWN



**ELECTRICAL TEST:**

- 1.100% OPEN&SHORT TEST
- 2.CONTACT RESISTANCE:20 Ohm (MAX)
- 3.INSULATION RESISTANCE:10 MOhm (MIN) DC 300V/10ms
- 4.Fluke Channel Test

COLOR	LENGTH(mm)	TOLERANCE
	300	±15
Grey; Blue; Green;	500	±15
Yellow; Orange;	1000	±20
Purple; Red; Black;	1500	±20
White	2000	±30
	3000	±30
	5000	±30

3	RJ45 PLUG:8P8C 3U" GOLD PLATED TWO-PIECE TOUGH PLUG NICKEL-PLATED SHELL.	
2	MOLDED: PVC MOLDED BOOT .	
1	CABLE:CAT6A U/FTP [32AWG(7/0.08BC)+AL/MYLA]*4+DRALN(7*0.08BC) OD=3.8±0.15MM LSZH JACKET. MARKING: CATEGORY 6A U/FTP SLIM PATCH CABLE LSZH AWG 32	
NO.	SPECIFICATION	Q'TY
	BOM LIST	

ITEM NO:	CAT6A U/FTP			DRAWER DATE	LY 20160829
TITLE				CHECKED DATE	MTC 20160829
CUSTOMER				APPROVED DATE	
MATERIAL	SCALE				
REV.	A	UNIT	MM		
DRAWING NO:					
ACAD FILE	E:\				