

ZYXEL

## Zyxel ATP200 laitteistopalomuuuri Työpöytä 2 Gbit/s

**Tuotemerkki :** Zyxel

**Tuotekoodi:** ATP200-EU0102F

**Tuotteen nimi :** ATP200

Zyxel ATP200. Palomuurin välityskyky: 2 Gbit/s, VPN-välityskyky: 0,5 Gbit/s, IPSec VPN throughput: 40 Gbit/s. Lämmön poisohjaus: 45,38 BTU/h, Keskimääräinen vikaantumisaika: 529688,2 h. Yhteysteknologia: Langallinen, Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s, WAN-portti: Ethernet (RJ-45). Kotelo: Työpöytä. Syöttöjännite: 2.5 A, Virrankulutus: 13,3 W



Data transmission		Design	
Firewall throughput *	2 Gbit/s	Rack mounting	✓
VPN throughput	0.5 Gbit/s	Form factor	Desktop
IPSec VPN throughput	40 Gbit/s	Built-in fan	✓
SSL performance	10 transactions/sec		
UTM throughput (fast/full scan)	450/450 Gbit/s		
Maximum connections (SPI)	2000		
HTTPS encryption	✓		
Performance		Power	
Heat dissipation	45.38 BTU/h	Input current	2.5 A
Mean time between failures (MTBF)	529688.2 h	Power consumption (typical)	13.3 W
Network		Certificates	
Number of VLANs	16	Certification	FCC Part 15 (Class B), CE EMC (Class B), C-Tick (Class B), BSMI, LVD (EN60950-1), BSMI
Active TCP connections (max)	600000		
Security		Operational conditions	
Stateful Packet Inspection (SPI)	✓	Operating temperature (T-T)	0 - 40 °C
Content filtering	1	Storage temperature (T-T)	-30 - 70 °C
		Operating relative humidity (H-H)	10 - 90%
		Storage relative humidity (H-H)	10 - 90%
Management features		Weight & dimensions	
LED indicators	✓	Dimensions (WxDxH)	272 x 187 x 36 mm
On/off switch	✓	Weight	1.4 kg
Ports & interfaces		Packaging data	
Connectivity technology	Wired	Package width	427 mm
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2	Package height	73 mm
Ethernet LAN (RJ-45) ports	4	Package depth	247 mm
Ethernet LAN data rates	10,100,1000 Mbit/s	Package weight	2.42 kg
Number of console ports	1		
WAN connection	Ethernet (RJ-45)		
Ethernet DMZ ports quantity	1		
SFP module slots quantity	1		
		Packaging content	
		Rack mount kit	✓
		Other features	
		Firewall throughput	2000 Mbit/s
		VPN throughput	500 Mbit/s
		Logistics data	
		Harmonized System (HS) code	85176990



4718937599240

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-DEC-2024. Prints or copies of Information are only valid on the printed Publication date