

ZYXEL

## Zyxel ATP500 laitteistopalomuuuri Työpöytä 2,6 Gbit/s

**Tuotemerkki :** Zyxel

**Tuotekoodi:** ATP500-EU0102F

**Tuotteen nimi :** ATP500

Zyxel ATP500. Palomuurin välityskyky: 2,6 Gbit/s, VPN-välityskyky: 0,9 Gbit/s. Lämmön poishjaus: 82,23 BTU/h, Keskimääräinen vikaantumisaika: 529688,2 h. Yhteysteknologia: Langallinen, Ethernet LAN - datanopeudet: 10,100,1000 Mbit/s. Kotelo: Työpöytä. Syöttöjännite: 4.17 A, Tehonkulutus (maks.): 24,1 W



| Data transmission                               |                    | Certificates                      |  |
|---|--------------------|-----------------------------------|--|
| Firewall throughput *                           | 2.6 Gbit/s         | Certification                     | FCC Part 15 (Class A), CE EMC (Class A), C-Tick (Class A), BSMI, LVD (EN60950-1), BSMI |
| VPN throughput                                  | 0.9 Gbit/s         |                                   |  |
| Performance                                     |                    | Operational conditions            |  |
| Heat dissipation                                | 82.23 BTU/h        | Operating temperature (T-T)       | 0 - 40 °C  |
| Mean time between failures (MTBF)               | 529688.2 h         | Storage temperature (T-T)         | -30 - 70 °C  |
| Network   |                    | Operating relative humidity (H-H) | 10 - 90%   |
| Number of VLANs                                 | 64                 | Storage relative humidity (H-H)   | 10 - 90%   |
| Active TCP connections (max)                    | 1000000            | Weight & dimensions               |  |
| Security  |                    | Dimensions (WxDxH)                | 300 x 188 x 44 mm  |
| Content filtering                               | 1                  | Weight                            | 1.65 kg  |
| Ports & interfaces                              |                    | Packaging data                    |  |
| Connectivity technology                         | Wired              | Package width                     | 351 mm   |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity | 2                  | Package height                    | 245 mm   |
| Ethernet LAN (RJ-45) ports                      | 7                  | Package depth                     | 152 mm   |
| Ethernet LAN data rates                         | 10,100,1000 Mbit/s | Package weight                    | 2.83 kg  |
| Design  |                    | Other features                    |  |
| Rack mounting                                   | ✓                  | Firewall throughput               | 2600 Mbit/s  |
| Form factor                                     | Desktop            | VPN throughput                    | 900 Mbit/s   |
| Power   |                    | Logistics data                    |  |
| Input current                                   | 4.17 A             | Harmonized System (HS) code       | 85176990   |
| Power consumption (max)                         | 24.1 W             |                                   |  |



4718937599264

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-DEC-2024. Prints or copies of Information are only valid on the printed Publication date