ATEN CS1148DP KVM-kytkin musta

Tuotemerkki : ATEN

Tuotekoodi: CS1148DP-AT-G


Tuotteen nimi : CS1148DP

ATEN CS1148DP. Näppäimistöportin liitin: USB, Hiiriportin liitin: USB, Videoportin tyyppi: DisplayPort. HDtyyppi: 4K Ultra HD, Enimmäiserottelutarkkuus: 3840 x 2160 pikseliä, Videokaistanleveys: 30 Hz. Tuotteen väri: musta, Kotelon materiaali: Metalli. Voimanlähde: AC, Tulojännite: 100 - 240 V, ACsyöttötaajuus: 50 - 60 Hz. Vaatimustenmukaisuustodistukset: RoHS



Ports & interfaces

Ports & interfacesSystem requirementsNumber of computers controlled *8Windows operating systems supported*Keyboard port type *USBSustalnabilityVide oport type *DisplayPortCompliance certificatesRoHSHDM ports quantity16Operating temperature (T-T)0 - 50 °CUSB 2.0 Type-B ports quantity16Operating temperature (T-T)0 - 60 %CConsole USB ports quantity2Operating relative humidity (H-H)0 - 80 %CUSB concertor typeUSB Type-BWidth20 + 00 °CUSB concertor typeUSB Type-BWidth0 + 00 °CUSB concertor typeUSB Type-BWidth20 + 9 mmAudi connections2 + 00 °C0 + 00 °C0 + 00 °CPortor and type *4 + 00 0 + 00 °C0 + 00 °CMaximum resolution*3 + 00 °C0 + 00 °C0 + 00 °CNation metsolution*3 + 00 °C0 + 00 °C0 + 00 °CNation metsolution*3 + 00 °C0 + 00 °C0 + 00 °CNation metsolution*3 + 00 °C0 + 00 °C0 + 00 °CNation metsolution*3 + 00 °C0 + 00 °C0 + 00 °CRack mounting *A0 + 00 °C0 + 00 °C0 + 00 °CPortor colon*No0 + 00 °C0 + 00 °C0 + 00 °CNoting materialMetal0 + 00 °C0 + 00 °C0 + 00 °CHD type *AA0 + 00 °C0 + 00 °C0 + 00 °CNoting materialNoNo0 + 00 °C0				
Keyboard port type *USBsupported ************************************	Ports & interfaces		System requirements	
Video port type *DisplayPortCompliance certificatesReHSHDM ports quantity2Compliance certificatesReHSLDS 2.0 Type-B ports quantity16Operating temperature (T-T)0.50 °CConsole ports *3.5mm headphone, HDMI, USB AStorage temperature (T-T)0.60 °CConsole USB ports quantity2Operating relative humidity (H-H)0.80%VISB 2.0 Type-B ports quantity2Operating relative humidity (H-H)0.80%VISB connector typeUSB Type-BWidth20.40 °CPS/2 ports quantity2Depth43.24 nmAudio connections*Depth43.24 nmPerformanceKUltra HDWeight3.54 kgMaximum resolution *3840 x 2160 pixelsPackage depth49 mmNationum resolution *Storage temperature (T-T)13.3 mmRack mounting *NataPackage depth49 mmProduct Color *BlackPackage depth49 mmProduct Color *Black409 mm42.14 mmHousing material*Package depth42.3 kgLE D indicators*Quick installation guideACPorterMautaColor *BlackMautaPorterMautaColor *BlackMautaHousing material*MautaColor *Sint *LE D indicators*MautaMautaColor *Porter*MautaSint *MautaPorter*MautaSint *<	I		1 5 5	1
HDMI per squantityProvide the conditionsFor any per standing of the conditionsDisplayPorts quantity16Operating temperature (T-T)0.50 °CConsole DSB ports quantity16Operating temperature (T-T)-20.60 °CConsole DSB ports quantity2Operating relative humidity (H-H)0.80%USB connector typeUSB Type-BWeight & dimensionsPS/2 ports quantity2Width204.9 mmAudio connections*Operating relative humidity (H-H)0.80%Performance-Height65.5 mmHD type *KK Ultra HDWeight3.54 kgMaximum resolution *3840 x 2160 pixelsPerkaging data3.54 kgNotice color *840 x 2160 pixelsPackage width133 mmNetsing materialNetalAcquing content4.23 kgPoduct colour *BlackPackaging content4.23 kgHousing materialMetalColes includedACDisplay*Quick installation guide*Power sourceACManual*Power sourceACMater (outer) case net weight10.6 kgPower sourceACMater (outer) case weight5176200AC input frequency50-60 HzMater (outer) case weight348 mmAC input frequency50-60 HzMater (outer) case weight348 mmAC input frequency1AMater (outer) case weight348 mmAC input frequency50-60 HzMater (outer) case weight348 mm <tr< td=""><td>Mouse port type *</td><td>USB</td><td>Sustainability</td><td></td></tr<>	Mouse port type *	USB	Sustainability	
DisplayPorts quantity16Operating temperature (T-T)0 - 50 °CUSB 2.0 Type-B ports quantity16Sorage temperature (T-T)0 - 60 °CConsole ports *3.5mm headphone, HDMI, USB ASorage temperature (T-T)0 - 80%Console USB ports quantity2Operating relative humidly (H-H)0 - 80%USB connector typeUSB Type-BWeight & dimensions24.4 mmAudio connector type15 Type-BWeight & dimensions432.4 mmAudio connections*Depth432.4 mmAudio connections*Weight0 - 80%Maximum resolution *3840 x 2160 pixelsWeight3.54 kgMaximum resolution *30 H2Package width133 mmPerformance*Package width133 mmVideo bandwidth30 H2Package width133 mmPerformance*Package width133 mmPorduct colour *Black244 mm423 kgHD type **Cales included4.23 kgPousing materialMetalCales included4.23 kgHD type **Cales included*Power **Cales included*Power sourceACManual*Input voltage100 - 240 VMaster (outer) case midth H21 case width10.6 kgAC input frequency50 - 60 H2Master (outer) case midth H21 case width134 mmInput current1AMaster (outer) case width427 mmInput current1AMaster (ou	1 21		Compliance certificates	RoHS
USB 2.0 Type-B ports quantity16Operating temperature (T-T)0 - 50 °CConsole ports *3.5mm headphone, HDMI, USB AStorage temperature (T-T)-20 - 60 °CConsole USB ports quantity2Operating relative humidity (H+H)0 - 80%USB connector typeUSB Ports quantity2Weight & dimensionsPS/2 ports quantity2Weight & dimensions432.4 mmAudio connectionsrDepth432.4 mmPerformanceKUItra HDWeight3.54 kgHD type *4K UItra HDWeight3.54 kgMaximum resolution *3840 x 2160 pixelsPackage depith133 mmPerformanceYacQue depithe132 mmVide bandwidth30 HZPackage depith324 mmPosignXPackage height324 mmRack mounting *XPackage height324 mmHousing materialMetalPackage weight4.23 kgHousing materialMetalConcoleManualLB indicatorsVColes includedACPower sourceACMaster (outer) case net weight10.6 kgPower sourceACHarmonized System (HS) code85176200Power consumption (typical)1AMaster (outer) case lengith348 mmPower consumption (typical)1AMaster (outer) case lengith348 mm			Operational conditions	
PS/2 ports quantity2Width204.9 mmAudio connections✓Depth432.4 mmAudio connections✓Depth432.4 mmPerformanceHeight65.5 mmHD type*4K Ultra HDWeight3.54 kgMaximum resolution*3840 x 2160 pixelsPackage width133 mmDesignPackage depth499 mmRack mounting*XPackage depth499 mmProduct colour *BlackPackage weight3.24 mmHousing materialMetalPackage content4.23 kgLED indicators✓Cables includedACDestign✓Quick installation guide✓Built-in display*XCables includedACPower sourceACManual0.6 kgInput voltage100 - 240 VMaster (outer) case net weight10.6 kgAC input frequency50 - 60 HzMaster (outer) case length519 mmInput current1AMaster (outer) case length519 mmInput current1AMaster (outer) case net weight11.6 kg	USB 2.0 Type-B ports quantity Console ports *	16 3.5mm headphone, HDMI, USB A	Storage temperature (T-T)	-20 - 60 °C
Audio connections*Depth204,9 minPerformanceDepth432,4 mmHD type *4K Ultra HDWeight3.54 kgMaximum resolution *3840 x 2160 pixelsPackaging data133 mmVideo bandwidth30 HzPackage weight499 mmPosignVackage depth499 mmPackage weight224 mmRack mounting *XPackage depth499 mmProduct colour *BlackPackage weight4.23 kgHousing materialMetalPackaging content4.23 kgLED indicatorsXCables includedACDisplayXQuick installation guide*Power sourceACMaster (outer) case weight10.6 kgPower sourceACMaster (outer) case weight427 mmAC input frequency50 - 60 HzMaster (outer) case length319 mmAC input frequency50 - 60 HzMaster (outer) case weight427 mmNower consumption (typical)15.3 WMaster (outer) case gross weight14.6 kg		USB Type-B	Weight & dimensions	
HormanicaWeight3.54 kgHD type *4K Ultra HDWeight3.54 kgMaximum resolution *3840 x 2160 pixelsPackaging dataVideo bandwidth30 HZPackage weight1.33 mmDesignPackage depth499 mmRack mounting *XPackage weight3.24 mmProduct colour *BlackAc2 kge weight3.24 mmHousing materialMetalPackage weight4.23 kgLED indicators*Cables includedACDisplay*Quick installation guide*Built-in display *XManual*PowerNoACMater (outer) case net weight1.06 kgNover sourceACMater (outer) case net weight6.5176200Input voltage100 - 240 VMaster (outer) case length519 mmAC input frequency50 - 60 HZMaster (outer) case length519 mmInput current1AMaster (outer) case net weight14.6 kg	Audio connections		Depth	432.4 mm
HD type*4K Ottra HDAreaMaximum resolution *3840 x 2160 pixelsPackaging dataVideo bandwidth30 HzPackage width133 mmDesignPackage depth499 mmRack mounting *×Package height324 mmProduct colour *BlackPackage weight4.23 kgHousing materialMetalPackaging content4.23 kgLED indicators•Cables includedACDisplay×Quick installation guide•Built-in display *×Logistics data•Power100 - 240 VMaster (outer) case net weight10.6 kgNow r sourceACMaster (outer) case net weight10.6 kgInput voltage100 - 240 VMaster (outer) case net weight5176200Input voltage10.6 HzMaster (outer) case net weight519 mmInput current1AMaster (outer) case height348 mmPower consumption (typical)15.3 WMaster (outer) case gross weight14.6 kg			•	
DesignPackage depth499 mmRack mounting *XPackage depth324 mmProduct colour *BlackPackage weight4.23 kgHousing materialMetalPackaging content4.23 kgLED indicatorsCables includedACDisplayQuick installation guideBuilt-in display *XManualPower </td <td>51</td> <td></td> <td>5</td> <td>5.54 kg</td>	51		5	5.54 kg
Package height324 mmRack mounting *×Product colour *BlackHousing materialMetalLED indicators✓Display✓Built-in display *×PowerACPower sourceACNow sourceACInput voltage100 - 240 VAC input frequency50 - 60 HzInput currentIAPower consumption (typical)IS3 W	Video bandwidth	30 Hz	Package width	
Rack mounting*XPackage weight4.23 kgProduct colour *BlackPackaging content	Design			
Housing material LED indicatorsMetalPackaging contentLED indicatorsCables includedACDisplayQuick installation guideBuilt-in display*XManualPowerCapistics data10.6 kgPower sourceACMaster (outer) case net weight10.6 kgInput voltage100 - 240 VMaster (outer) case width427 mmAC input frequency50 - 60 HzMaster (outer) case length519 mmInput current1AMaster (outer) case net weight519 mmPower consumption (typical)15.3 WMaster (outer) case gross weight348 mm			5 5	
Display Quick installation guide Image: Construction of the second seco			Packaging content	
Display Manual Manual Built-in display* × Power Logistics data Power source AC Input voltage 100 - 240 V AC input frequency 50 - 60 Hz Input current 1A Power consumption (typical) 15.3 W	LED indicators	1	Cables included	AC
Built-in display* × Manual ✓ Power	Display		Quick installation guide	✓
PowerACMaster (outer) case net weight10.6 kgPower sourceACHarmonized System (HS) code85176200Input voltage100 - 240 VMaster (outer) case width427 mmAC input frequency50 - 60 HzMaster (outer) case length519 mmInput current1 AMaster (outer) case height348 mmPower consumption (typical)15.3 WMaster (outer) case gross weight14.6 kg	Built-in display *	×	Manual	✓
Power sourceACMaster (outer) case net weight10.6 kgInput voltage100 - 240 VHarmonized System (HS) code85176200AC input frequency50 - 60 HzMaster (outer) case width427 mmInput current1 AMaster (outer) case length519 mmPower consumption (typical)15.3 WMaster (outer) case gross weight14.6 kg	Power		Logistics data	
	Power source Input voltage AC input frequency Input current	100 - 240 V 50 - 60 Hz 1 A	Harmonized System (HS) code Master (outer) case width Master (outer) case length Master (outer) case height Master (outer) case gross weight	85176200 427 mm 519 mm 348 mm 14.6 kg



4719264646690

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.