



D-Link DMC-G01LC/E network media converter 1000 Mbit/s Grey

Brand : D-Link

Product code: DMC-G01LC/E

Product name : DMC-G01LC/E



10/100/1000 to SFP Media Converter, EU Plug

D-Link DMC-G01LC/E. Maximum data transfer rate: 1000 Mbit/s, Networking standards: IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, Ethernet interface type: Gigabit Ethernet. Mean time between failures (MTBF): 506711 h. Product colour: Grey. Fiber optic connector: SFP, Connectivity technology: Wired. Input voltage: 230 - 240 V, Output voltage: 5 V, Output current: 1 A



Network		Operational conditions	
Maximum data transfer rate *	1000 Mbit/s	Storage relative humidity (H-H)	5 - 90%
Networking standards	IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x	Packaging data	
Ethernet interface type	Gigabit Ethernet	Package width	101 mm
Ethernet LAN data rates	10,100,1000 Mbit/s	Package depth	134 mm
Auto MDI/MDI-X	✓	Package height	95 mm
Performance		Package weight	358 g
Mean time between failures (MTBF)	506711 h	Certificates	
Features		Safety	LVD, UL/cUL
Internal *	✗	Certification	CE, FCC, VCCI, BSMI
LED indicators	✓	Logistics data	
Product colour	Grey	Shipping (inner) case length	50.4 cm
Ports & interfaces		Shipping (inner) case width	29.4 cm
Connectivity technology	Wired	Shipping (inner) case height	23.6 cm
Ethernet LAN (RJ-45) ports	1	Shipping (inner) case net weight	7.16 kg
Fiber ports quantity	1	Products per shipping (inner) case	20 pc(s)
Fiber optic connector *	SFP	Pallet gross weight (air)	341.1 kg
DC-in jack	✓	Master (outer) cases per pallet (air)	40 pc(s)
Power		Products per pallet (air)	800 pc(s)
Input voltage	230 - 240 V	Pallet gross length	110 cm
Output voltage	5 V	Pallet gross width	120 cm
Output current	1 A	Pallet height (air)	131 cm
Weight & dimensions		Pallet gross weight (sea)	534.6 kg
Width	70 mm	Master (outer) cases per pallet (sea)	64 pc(s)
Depth	95 mm	Products per pallet (sea)	1280 pc(s)
Height	25 mm	Pallet height (sea)	2.02 m
Operational conditions		Shipping (inner) case gross weight	8.04 kg
Operating temperature (T-T)	0 - 50 °C	Harmonized System (HS) code	85176990
Storage temperature (T-T)	-10 - 70 °C		
Operating relative humidity (H-H)	10 - 90%		



0790069415982



790069415982

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.