

D-Link DMC-G01LC/E verkon mediamuunnin 1000 Mbit/s Harmaa

Tuotemerkki : D-Link

Tuotekoodi: DMC-G01LC/E

Tuotteen nimi : DMC-G01LC/E



D-Link DMC-G01LC/E. Tiedonsiirron enimmäisnopeus: 1000 Mbit/s, Verkkostandardit: IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, Ethernet-liitännän tyyppi: Gigabit Ethernet. Keskimääräinen vikaantumisaika: 506711 h. Tuotteen väri: Harmaa. Valokuituliitin: SFP, Yhteysteknologia: Langallinen. Tulojännite: 230 - 240 V, Ulostulojännite: 5 V, Lähtövirta: 1 A



Network		Operational conditions	
Maximum data transfer rate *	1000 Mbit/s	Storage relative humidity (H-H)	5 - 90%
Networking standards	IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x	Packaging data	
Ethernet interface type	Gigabit Ethernet	Package width	101 mm
Ethernet LAN data rates	10,100,1000 Mbit/s	Package depth	134 mm
Auto MDI/MDI-X	✓	Package height	95 mm
		Package weight	358 g
Performance		Certificates	
Mean time between failures (MTBF)	506711 h	Safety	LVD, UL/cUL
		Certification	CE, FCC, VCCI, BSMI
Features		Logistics data	
Internal *	✗	Shipping (inner) case length	50.4 cm
LED indicators	✓	Shipping (inner) case width	29.4 cm
Product colour	Grey	Shipping (inner) case height	23.6 cm
		Shipping (inner) case net weight	7.16 kg
Ports & interfaces		Products per shipping (inner) case	20 pc(s)
Connectivity technology	Wired	Pallet gross weight (air)	341.1 kg
Ethernet LAN (RJ-45) ports	1	Master (outer) cases per pallet (air)	40 pc(s)
Fiber ports quantity	1	Products per pallet (air)	800 pc(s)
Fiber optic connector *	SFP	Pallet gross length	110 cm
DC-in jack	✓	Pallet gross width	120 cm
		Pallet height (air)	131 cm
Power		Pallet gross weight (sea)	534.6 kg
Input voltage	230 - 240 V	Master (outer) cases per pallet (sea)	64 pc(s)
Output voltage	5 V	Products per pallet (sea)	1280 pc(s)
Output current	1 A	Pallet height (sea)	2.02 m
		Shipping (inner) case gross weight	8.04 kg
Weight & dimensions		Harmonized System (HS) code	85176990
Width	70 mm		
Depth	95 mm		
Height	25 mm		
Operational conditions			
Operating temperature (T-T)	0 - 50 °C		
Storage temperature (T-T)	-10 - 70 °C		
Operating relative humidity (H-H)	10 - 90%		



0790069415982



790069415982

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.