

ASUS ProArt PA24AC computer monitor 61.2 cm (24.1") 1920 x 1200 pixels WUXGA LED Silver

Brand : ASUS

Product family: ProArt

Product code: 90LM04B0-B01370

Product name : PA24AC

- 24-inch WUXGA 1920 x 1200 IPS display with frameless design
 - 100% of sRGB color gamut, pre-calibrated for excellent color accuracy ($\Delta E < 2$)
 - Support HDR-10 presents HDR (High Dynamic Range) performance
 - ASUS ProArt Calibration technology offers advanced adjustments
 - I/O ports: DP over USB-C™ with 60W Power Delivery, DisplayPort, HDMI, USB 3.0 hub
- 24.1" WUXGA (1920 x 1200) IPS, 16:10, 350 cd/m, 5ms, 100M:1, HDMI(v2.0a) x2, DisplayPort 1.2, USB , 2x2W
- ASUS ProArt PA24AC. Display diagonal: 61.2 cm (24.1"), Display resolution: 1920 x 1200 pixels, HD type: WUXGA, Display technology: LED, Response time: 5 ms, Native aspect ratio: 16:10, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Silver

Display		Ergonomics	
Display diagonal *	61.2 cm (24.1")	VESA mounting *	✓
Display resolution *	1920 x 1200 pixels	Panel mounting interface	100 x 100 mm
HD type *	WUXGA	Cable lock slot *	✓
Native aspect ratio *	16:10	Cable lock slot type	Kensington
Display technology *	LED	Height adjustment *	✓
Panel type *	IPS	Height adjustment	11 cm
Touchscreen *	✗	Pivot	✓
Display brightness (typical)	350 cd/m ²	Pivot angle	-90 - 90°
Response time *	5 ms	Swivelling	✓
Screen shape *	Flat	Swivel angle range	-45 - 45°
Supported graphics resolutions	1920 x 1200 (WUXGA)	Tilt adjustment	✓
Contrast ratio (typical) *	1000:1	Tilt angle range	-5 - 23°
Contrast ratio (dynamic)	100000000:1	Picture-in-Picture	✓
Maximum refresh rate *	70 Hz	LED indicators	✓
Viewing angle, horizontal	178°	Power	
Viewing angle, vertical	178°	Energy efficiency class (SDR) *	G
Display number of colours *	16.78 million colours	Energy efficiency class (HDR) *	G
Viewable size, horizontal	51.8 cm	Energy consumption (SDR) per 1000 hours *	28 kWh
Viewable size, vertical	32.4 cm	Energy consumption (HDR) per 1000 hours *	29 kWh
Digital horizontal frequency	30 - 85 kHz	Power consumption (standby) *	0.5 W
Digital vertical frequency	48 - 70 Hz	Power consumption (off)	0.3 W
High Dynamic Range (HDR) supported	✓	AC input voltage	100 - 240 V
High Dynamic Range (HDR) technology	High Dynamic Range (HDR) 400	AC input frequency	50 - 60 Hz
Colour depth	8 bit	Energy efficiency scale	A to G
Colour gamut standard	sRGB	European Product Registry for Energy Labelling (EPREL) code	387775
sRGB coverage (typical)	100%	Operational conditions	
3D	✗	Operating temperature (T-T)	0 - 40 °C
Performance		Storage temperature (T-T)	-20 - 60 °C
NVIDIA G-SYNC *	✗	Weight & dimensions	
AMD FreeSync *	✗	Width (with stand)	532 mm
VESA Adaptive Sync support	✓	Depth (with stand)	202 mm
Flicker-free technology	✓	Height (with stand)	378 mm
Low Blue Light technology	✓	Weight (with stand)	6.5 kg
Multimedia		Width (without stand)	532 mm
Number of speakers	2		

Multimedia		Weight & dimensions	
RMS rated power	4 W	Depth (without stand)	55 mm
Built-in speaker(s) *	✓	Height (without stand)	349 mm
Built-in camera *	✗	Weight (without stand)	4.28 kg
Design		Height (max)	48.8 cm
Market positioning *	Graphics design	Packaging data	
Product colour *	Silver	Package width	650 mm
Frameless design	✓	Package depth	430 mm
Feet colour	Silver	Package height	260 mm
Ports & interfaces		Package weight	9 kg
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Package type	Box
USB upstream port type	USB Type-C	Packaging content	
Number of upstream ports	1	Stand included	✓
Number of USB Type-C upstream ports quantity	1	Cables included	AC
USB Type-A downstream ports quantity	4	Manual	✓
USB Type-C downstream ports quantity	1	Other features	
DVI port	✗	On/off switch	✓
HDMI ports quantity	2	Rotating	✗
HDMI version	2.0a	TV tuner integrated	✗
DisplayPorts quantity	1	Picture-by-Picture (PbP)	✓
DisplayPort version	1.2	Certification	Energy Star®, BSMI, CB, CCC, CEL level , CU, ErP, FCC, ISO-9241-307, J-MOSS, KCC, Mac CompliantPSE, TCO7.0, UkrSEPRO, UL/cUL, VCCI, WEEE, WHQL , MEPS, TUV Flicker-free , KC , eStandby, TUV Low Blue Light, Vietnam MEPS, ICES-3, RCM, VESA DisplayHDR 400
Headphone out *	✓		
Headphone outputs	1	Logistics data	
HDCP	✓	Harmonized System (HS) code	85285210
AC (power) in	✓		



4718017080835



0192876088111



192876088111



4718017080804

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.