

## ASUS ProArt PA24AC tietokoneen litteä näyttö 61,2 cm (24.1") 1920 x 1200 pikseliä WUXGA LED Hopea

**Tuotemerkki :** ASUS

**Tuoteperhe:** ProArt

**Tuotekoodi:** 90LM04B0-  
B01370

**Tuotteen nimi :** PA24AC

ASUS ProArt PA24AC. Näytön halkaisija: 61,2 cm (24.1"), Näytön erottelutarkkuus: 1920 x 1200 pikseliä, HD-tyyppi: WUXGA, Näytön teknologia: LED, Vasteaika (tyypillinen): 5 ms, Vakiokuvausuhde: 16:10, Katselukulma, vaakasuora: 178°, Katselukulma, pystysuora: 178°. Sisäiset kaiuttimet. USB-keskuksen versio: 3.2 Gen 1 (3.1 Gen 1). VESA-kiinnitys, Korkeudensäätö. Tuotteen väri: Hopea

| Display                             |                              | Ergonomics  |              |
|-------------------------------------|------------------------------|---|--------------|
| Display diagonal *                  | 61.2 cm (24.1")              | VESA mounting *   | ✓            |
| Display resolution *                | 1920 x 1200 pixels           | Panel mounting interface                                    | 100 x 100 mm |
| HD type *                           | WUXGA                        | Cable lock slot *   | ✓            |
| Native aspect ratio *               | 16:10                        | Cable lock slot type  | Kensington   |
| Display technology *                | LED                          | Height adjustment *   | ✓            |
| Panel type *                        | IPS                          | Adjustable height (max)                                     | 11 cm        |
| Touchscreen *                       | ✗                            | Pivot   | ✓            |
| Display brightness (typical)        | 350 cd/m <sup>2</sup>        | Pivot angle   | -90 - 90°    |
| Response time *                     | 5 ms                         | Swivelling  | ✓            |
| Screen shape *                      | Flat                         | Swivel angle range  | -45 - 45°    |
| Supported graphics resolutions      | 1920 x 1200 (WUXGA)          | Tilt adjustment   | ✓            |
| Contrast ratio (typical) *          | 1000:1                       | Tilt angle range  | -5 - 23°     |
| Contrast ratio (dynamic)            | 100000000:1                  | Picture-in-Picture  | ✓            |
| Maximum refresh rate *              | 70 Hz                        | LED indicators  | ✓            |
| Viewing angle, horizontal           | 178°                         |   |              |
| Viewing angle, vertical             | 178°                         |   |              |
| Display number of colours *         | 16.78 million colours        | Power   |              |
| Viewable size, horizontal           | 51.8 cm                      | Energy efficiency class (SDR) *                             | G            |
| Viewable size, vertical             | 32.4 cm                      | Energy efficiency class (HDR) *                             | G            |
| Digital horizontal frequency        | 30 - 85 kHz                  | Energy consumption (SDR) per 1000 hours *                   | 28 kWh       |
| Digital vertical frequency          | 48 - 70 Hz                   | Energy consumption (HDR) per 1000 hours *                   | 29 kWh       |
| High Dynamic Range (HDR) supported  | ✓                            | Power consumption (standby) *                               | 0.5 W        |
| High Dynamic Range (HDR) technology | High Dynamic Range (HDR) 400 | Power consumption (off)                                     | 0.3 W        |
| Colour depth                        | 8 bit                        | AC input voltage  | 100 - 240 V  |
| Colour gamut standard               | sRGB                         | AC input frequency  | 50 - 60 Hz   |
| sRGB coverage (typical)             | 100%                         | Energy efficiency scale                                     | A to G       |
| 3D                                  | ✗                            | European Product Registry for Energy Labelling (EPREL) code | 387775       |
| Performance                         |                              | Operational conditions                                      |              |
| NVIDIA G-SYNC *                     | ✗                            | Operating temperature (T-T)                                 | 0 - 40 °C    |
| AMD FreeSync *                      | ✗                            | Storage temperature (T-T)                                   | -20 - 60 °C  |
| VESA Adaptive Sync support          | ✓                            | Weight & dimensions   |              |
| Flicker-free technology             | ✓                            | Width (with stand)  | 532 mm       |
| Low Blue Light technology           | ✓                            | Depth (with stand)  | 202 mm       |
| Multimedia                          |                              | Height (with stand)   | 378 mm       |
| Number of speakers                  | 2                            | Weight (with stand)   | 6.5 kg       |
| RMS rated power                     | 4 W                          | Width (without stand)                                       | 532 mm       |
| Built-in speaker(s) *               | ✓                            | Depth (without stand)                                       | 55 mm        |
| Built-in camera *                   | ✗                            | Height (without stand)                                      | 349 mm       |
| Design                              |                              | Weight (without stand)                                      | 4.28 kg      |
| Market positioning *                | Graphics design              | Height (max)  | 48.8 cm      |

| Design                                       |                       | Packaging data              |  |
|--|-----------------------|-----------------------------|--|
| Product colour *                             | Silver                | Package width               | 650 mm   |
| Frameless design                             | ✓                     | Package depth               | 430 mm   |
| Feet colour                                  | Silver                | Package height              | 260 mm   |
| Ports & interfaces                           |                       | Package weight              | 9 kg   |
| USB hub version                              | 3.2 Gen 1 (3.1 Gen 1) | Package type                | Box  |
| USB upstream port type                       | USB Type-C            | Packaging content           |  |
| Number of upstream ports                     | 1                     | Stand included              | ✓  |
| Number of USB Type-C upstream ports quantity | 1                     | Cables included             | AC   |
| USB Type-A downstream ports quantity         | 4                     | Manual                      | ✓  |
| USB Type-C downstream ports quantity         | 1                     | Other features              |  |
| DVI port                                     | ✗                     | On/off switch               | ✓  |
| HDMI ports quantity                          | 2                     | Rotating                    | ✗  |
| HDMI version                                 | 2.0a                  | TV tuner integrated         | ✗  |
| DisplayPorts quantity                        | 1                     | Picture-by-Picture (PbP)    | ✓  |
| DisplayPort version                          | 1.2                   | Certification               | Energy Star®, BSMI, CB, CCC, CEL level , CU, ErP, FCC, ISO-9241-307, J-MOSS, KCC, Mac ComplianPSE, TCO7.0, UkrSEPRO, UL/cUL, VCCI, WEEE, WHQL , MEPS, TUV Flicker-free , KC , eStandby, TUV Low Blue Light, Vietnam MEPS, ICES-3, RCM, VESA DisplayHDR 400 |
| Headphone out *                              | ✓                     |                             |  |
| Headphone outputs                            | 1                     | Logistics data              |  |
| HDCP   | ✓                     | Harmonized System (HS) code | 85285210   |
| AC (power) in                                | ✓                     |                             |  |



4718017080835



0192876088111



192876088111



4718017080804

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.