

## Chieftec PowerPlay virtalähdeyksikkö 850 W 20+4 pin ATX PS/2 musta, Punainen

**Tuotemerkki :** Chieftec

**Tuotekoodi:** GPU-850FC

**Tuotteen nimi :** PowerPlay

Chieftec PowerPlay. Kokonaisteho: 850 W, AC-syöttöjännite: 100 - 240 V, AC-syöttötaajuus: 47 - 63 Hz. Emolevyn virtaliitin: 20+4 pin ATX, Emolevyn virtapiuhan pituus: 60 cm, SATA-virtakaapelin pituus: 150,800 mm. Tarkoitus: PC, Virransyöttöyksikön mitat: PS/2, 80 PLUS certification: 80 PLUS Platinum. Tuotteen väri: musta, Punainen, Jäähdytyksen tyyppi: Aktiivinen, Tuulettimen halkaisija: 14 cm. Tuotteen leveys: 150 mm, Tuotteen syvyys: 160 mm, Tuotteen korkeus: 86 mm



| Power   |  | Ports & interfaces                     |                  |
|---|--|--|------------------|
| Total power *                                 | 850 W  | PCI Express power connectors (6+2 pin) | 6                |
| AC input voltage *                            | 100 - 240 V  | PCI Express power cable length         | 60 cm            |
| AC input frequency                            | 47 - 63 Hz   | ATX power connector (20+4 pin)         | ✓                |
| Input current                                 | 12 A   | Floppy drive power connector           | 1                |
| Power factor                                  | 0.9  | Floppy disk drive connector            | ✓                |
| Power Factor Correction (PFC) type            | Active   | PCI Express connector                  | ✓                |
| Combined power (+3.3V)                        | 100 W  | Cabling type                           | Fully-Modular    |
| Combined power (+12V)                         | 849.96 W   | Performance                            |                  |
| Combined power (+5V)                          | 100 W  | 80 PLUS certification *                | 80 PLUS Platinum |
| Combined power (-12V)                         | 3.6 W  | Purpose *                              | PC               |
| Combined power (+5Vsb)                        | 15 W   | Power supply unit (PSU) form factor *  | PS/2             |
| Max output current (+3.3V)                    | 100 A  | ATX version                            | 2.3              |
| Max output current (+12V)                     | 70.83 A  | Design                                 |                  |
| Max output current (+5V)                      | 20 A   | Product colour                         | Black, Red       |
| Max output current (-12V)                     | 0.3 A  | Cooling type                           | Active           |
| Max output current (+5Vsb)                    | 3 A  | Fan diameter                           | 14 cm            |
| Power protection features                     | Over current, Over power, Over voltage, Overheating, Short circuit | Number of fans                         | 1 fan(s)         |
|   |  | Fan location                           | Top              |
| Ports & interfaces                            |  | On/off switch                          | ✓                |
| Motherboard power connector *                 | 20+4 pin ATX   | Weight & dimensions                    |                  |
| Motherboard power cable length                | 60 cm  | Width                                  | 150 mm           |
| Number of SATA power connectors               | 9  | Depth                                  | 160 mm           |
| SATA power cable length                       | 150,800 mm   | Height                                 | 86 mm            |
| Peripheral (Molex) power connectors (4-pin) * | 3  | Weight                                 | 3.41 kg          |
| Peripheral (Molex) power cable length         | 150,700 mm   | Packaging data                         |                  |
| EPS power connector (8-pin)                   | ✓  | Package weight                         | 3.82 kg          |

**Packaging data**

|              |     |
|--------------|-----|
| Package type | Box |
|--------------|-----|

**Logistics data**

|                             |          |
|-----------------------------|----------|
| Harmonized System (HS) code | 84733020 |
|-----------------------------|----------|



0753263076090



753263076090

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.