Chieftec Photon virtalähdeyksikkö 750 W 24-pin ATX PS/2 musta

Tuotemerkki : Chieftec Tuotekoodi: CTG-750C-RGB

Tuotteen nimi: Photon

Chieftec Photon. Kokonaisteho: 750 W, AC-syöttöjännite: 230 V, AC-syöttötaajuus: 50 Hz. Emolevyn virtaliitin: 24-pin ATX, Emolevyn virtapiuhan pituus: 55 cm, SATA-virtakaapelin pituus: 150,450 mm. Tarkoitus: PC, Virransyöttöyksikön mitat: PS/2, Tuetut emolevyt: ATX. Tuotteen väri: musta, Jäähdytyksen tyyppi: Aktiivinen, Tuulettimen halkaisija: 12 cm. Tuotteen leveys: 150 mm, Tuotteen syvyys: 140 mm, Tuotteen korkeus: 87 mm





| Power | | Ports & interfaces | | |
|--|---|---|--|------------------|
| Total power * AC input voltage * AC input frequency Input current Combined power (+3.3V) Combined power (+5V) Combined power (-12V) | 750 W 230 V 50 Hz 6.3 A 130 W 130 W 3.6 W | CPU power connector (4+4 pin) CPU power cable length ATX Power connector (24-pin) Floppy drive power connector Floppy disk drive connector Cabling type | ✓60 cm✓2✓Semi-Modular | |
| Max output current (+3.3V) | 22 A | Performance | | |
| Max output current (+12V1) Max output current (+12V2) | 30 A 30 A | Supported motherboard form factors | ATX | |
| Max output current (+5V) | 22 A | Purpose * | PC | |
| Max output current (-12V) | 0.3 A | Power supply unit (PSU) form factor * | PS/2 | |
| Efficiency Power protection features | 85% Over voltage, Overload, Short circuit, Under voltage | Design | | |
| | | Product colour | Black | |
| Ports & interfaces | | Cooling type | Active | |
| Motherboard power connector * Motherboard power cable length Number of SATA power connectors SATA power cable length | 24-pin ATX 55 cm 6 150,450 mm | Fan diameter Number of fans Fan location Illumination | 12 cm 1 fan(s) Top ✓ | |
| Peripheral (Molex) power connectors (4-pin) * | 4 | Weight & dimensions | | |
| Peripheral (Molex) power cable length | 150,450 mm ² 4 | 150,450 mm Depth | Depth | 150 mm 140 mm |
| PCI Express power connectors (6+2 pin) 4 | | Height Weight | 87 mm 2.15 kg | |
| PCI Express power cable length | 55 cm | Logistics data | | |
| | | Harmonized System (HS) code | 84733020 | |

| _ | | | • | | |
|---|----|----|-----|-----|-----|
| u | τn | er | теа | ıτu | res |

Illumination colour

Blue, Green, Red





753263075925

0753263075925

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.