


APC SRV3KRI UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 3 kVA 2400 W 7 AC-pistorasia(a)

Tuotemerkki : APC Tuotekoodi: SRV3KRI

Tuotteen nimi: SRV3KRI







Features		Ports & interfaces	
UPS topology *	Double-conversion (Online)	SmartSlot	✓
Output power capacity *	3 kVA	Battery	
Output power *	2400 W	Battery technology	Sealed Lead Acid (VRLA)
Waveform *	Sine	Battery recharge time	4 h
Input operation voltage (min) *	160 V 280 V	Automatic battery test	✓
Input operation voltage (max) * Input frequency *	40/70 Hz	,	
Output operation voltage (min)	220 V	Design	
Output operation voltage (max)	240 V	Form factor *	Rackmount
Output frequency	50/60 Hz	Rack capacity	1U
Output voltage regulation	1%	Product colour *	Black LCD
Surge energy rating	600	Display type	LCD ✓
Transfer time (Line Mode to Battery	0 ms	LED indicators	
Mode)	O MS	Certification	CE, IEC 62040-1-1, IEC 62040-1-2 REACH
Number of input phases	1	One wational conditions	
Number of output phases	1	Operational conditions	
Efficiency	88%	Operating temperature (T-T)	0 - 40 °C
Input power factor	0.95	Storage temperature (T-T)	-20 - 50 °C
Output power factor	0.8	Operating relative humidity (H-H)	0 - 95%
Crest factor	3:1	Storage relative humidity (H-H)	0 - 95%
ECO mode	✓	Operating altitude Non-operating altitude	0 - 3000 m 0 - 14763.6 m
Emergency Power Off (EPO)	×		0 - 14703.0 III
Output voltage Total Harmonic Distortion (THD)	3% 50 dB	Technical details Compliance certificates	RoHS
Noise level			KUIIS
Audible alarm(s)	✓	Weight & dimensions	
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm	Width Depth	437 mm 632 mm
Auto-restart	✓	Height	86 mm
Maintenance-free	·	Weight	27.6 kg
	•	Package width	569 mm
Socket circuit breaker	✓	Package depth	795 mm
Ports & interfaces		Package height	229 mm
AC outlet types	C13 coupler, C19 coupler	Package weight	29 kg
AC outlets quantity	7 AC outlet(s)	Packaging data	
USB port	✓ USB Type-B	Cables included	USB cable
USB port type		Manual	✓
Serial interface	✓		
Serial ports quantity	1	Software CD	✓
		Logistics data	
		Harmonized System (HS) code	85078000

O +l	har	fost	ures
UL	II EI	ıeaı	ures

Nominal output voltage 230 V Nominal input voltage 230 V





731304341734

0731304341734

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.