BenQ MU613 data projector Standard throw projector 4000 ANSI lumens DLP WUXGA (1920x1200) White

Brand : BenQ

Product name : MU613

Product code: 9H.JKX77.13E

- 4,000 ANSI Lumen High Brightness for Stunning Presentations
- WUXGA Resolution and Infographic Mode for Crisp Readability
- Highly Compatible Connectivity

MU613, 1920x1200, DLP 0.47", 4000 lum, 16:10, RMS 2W, VGA, HDMI, 3.5mm, USB, RS-232, AC 100-240V, 50/60Hz, 312x225x222 mm

BenQ MU613. Projector brightness: 4000 ANSI lumens, Projection technology: DLP, Projector native resolution: WUXGA (1920x1200). Light source type: Lamp, Service life of light source: 4000 h, Service life of light source (economic mode): 10000 h. Focus: Manual, Focal length range: 15.843 - 17.445 mm, Aperture range (F-F): 2 - 2.05. Supported graphics resolutions: 640 x 480 (VGA), 1920 x 1200 (WUXGA), Supported video modes: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p. Serial interface type: RS-232, HDMI connector type: Full-size

Projector

Screen size compatibility *	762 - 7620 mm (30 - 300")
Projector brightness *	4000 ANSI lumens
Projection technology *	DLP
Projector native resolution *	WUXGA (1920x1200)
Contrast ratio (typical) *	10000:1
Native aspect ratio *	16:10
Number of colours	1.073 billion colours
Horizontal scan range	15 - 102 kHz
Vertical scan range	23 - 120 Hz
Keystone correction, vertical	-40 - 40°
Matrix size	1.19 cm (0.47")
Matrix type	DMD

Light source

Light source type *	Lamp
Service life of light source *	4000 h
Service life of light source (economic mode)	10000 h
Lamp power	245 W
Lamps quantity	1 lamp(s)

Lens system

Focus *	Manual
Focal length range	15.843 - 17.445 mm
Aperture range (F-F)	2 - 2.05
Zoom capability	✔
Zoom type	Manual
Zoom ratio	1.1:1
Throw ratio	1.5 - 1.65
Offset	100%

Video

Full HD *	✔
Supported graphics resolutions	640 x 480 (VGA), 1920 x 1200 (WUXGA)

Network

Smart TV *	✘
Ethernet LAN *	✘
Wi-Fi *	✘

Storage

Card reader integrated *	✘

Multimedia

Built-in speaker(s) *	✔
RMS rated power	2 W
Number of built-in speakers	1

Design

Market positioning *	Presentation
Product type *	Standard throw projector
Product colour *	White
Placement	Desktop
Cable lock slot	✔
Cable lock slot type	Kensington

Display

Built-in display *	✘

Power

Power source *	AC
Power consumption (typical) *	110 W
Power consumption (standby) *	0.5 W
Power consumption (max)	260 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	10 - 90%

Video

Supported video modes	480i, 480p, 576i, 576p, 720p, 1080i, 1080p

Ports & interfaces

HDMI connector type	Full-size
USB 2.0 ports quantity *	1
Serial interface type *	RS-232
PC Audio in	✔
PC Audio out	✔
VGA (D-Sub) ports quantity *	2
HDMI ports quantity *	2
DVI port *	✘
Mobile High-Definition Link (MHL)	✔
AC (power) in	✔

Operational conditions

Storage relative humidity (H-H)	10 - 90%
Operating altitude	0 - 1499 m

Weight & dimensions

Width	312 mm
Depth	225 mm
Height	110 mm
Weight *	2.63 kg

Packaging content

Remote control included *	✔
Batteries included	✔
Cables included	AC, VGA
Manual	✔

Logistics data

Harmonized System (HS) code	85286200

4718755077838