

## APC SY96K160H-NB UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 160 kVA 160000 W

Tuotemerkki : APC

Tuotekoodi: SY96K160H-NB



Tuotteen nimi : SY96K160H-NB

APC SY96K160H-NB. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 160 kVA, Lähtöteho: 160000 W. Pistorasian tyypit: Hard Wire 5-wire (3PH + N + G). Kotelo: Tower, Tuotteen väri: musta, Telineen kapasiteetti: 42U. Tuotteen leveys: 600 mm, Tuotteen syvyys: 1070 mm, Tuotteen korkeus: 1991 mm

Features		Ports & interfaces	
UPS topology *	Double-conversion (Online)	SmartSlot	✓
Output power capacity * Output power *	160 kVA 160000 W	Design	
Waveform *SineInput operation voltage (min) *340 VInput operation voltage (max) *477 VInput frequency *40/70 HzOutput operation voltage (min)230 VOutput operation voltage (max)415 VOutput frequency50/60 Hz	Sine 340 V 477 V 40/70 Hz 230 V 415 V	Form factor * Rack capacity Product colour * Display type LED indicators International Protection (IP) code Certification	Tower 42U Black LCD ✓ IP20 EN 50091-1, EN/IEC 62040-1-1, EN/IEC 62040-2, EN/IEC 62040-3, EO 1000 1000 1000 1000 1000 1000 1000
Maximum current	current 197 A f output phases 3 95% er factor 0.99 cy Power Off (EPO) Itage Total Harmonic (THD) 5%	Operational conditions	ISO 14001, ISO 9001, VFI-SS-111
Efficiency Input power factor Emergency Power Off (EPO) Output voltage Total Harmonic Distortion (THD) Input current Total Harmonic		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -15 - 40 °C 0 - 95% 0 - 95% 0 - 1000 m 0 - 15000 m
Distortion (THD)	5%	Weight & dimensions	
Noise level Power protection features Audible alarm(s) Audible alarm modes Ports & interfaces	63 dB Overload, Short circuit ✓ Alarm when on battery, Low battery alarm	Width Depth Height Weight Package width	600 mm 1070 mm 1991 mm 496 kg 848 mm 1210 mm
AC outlet types	Hard Wire 5-wire (3PH + N + G)	Package depth Package height	2140 mm
RS-232 ports	1	Package weight	547 kg
		Packaging data	
		Manual	,

Manual

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.