



APC SMT3000RMI2UC UPS-virtalähde Linjainteraktiivinen 3 kVA 2700 W 9 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SMT3000RMI2UC

Tuotteen nimi : SMT3000RMI2UC



APC SMT3000RMI2UC. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 3 kVA, Lähtöteho: 2700 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: C20 liitin, Ulostulojen määrä: 9 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 547 VAH, Tyypillinen varmuuskopioaika täydellä kuormituksella: 3,2 min. Kotelo: Telineasennettava, Tuotteen väri: musta, Telineen kapasiteetti: 2U. Tuotteen leveys: 432 mm, Tuotteen syvyys: 683 mm, Tuotteen korkeus: 86 mm




| Features | | Battery | |
|------------------------------------|--------------------------|-----------------------------------|---|
| UPS topology * | Line-Interactive | Cold start | ✓ |
| Output power capacity * | 3 kVA | Design | |
| Output power * | 2700 W | Form factor * | Rackmount |
| Waveform * | Sine | Rack capacity | 2U |
| Input operation voltage (min) * | 151 V | Cable length | 2 m |
| Input operation voltage (max) * | 302 V | Product colour * | Black |
| Input frequency * | 50/60 Hz | Display type | LCD |
| Output operation voltage (min) | 220 V | LED indicators | Status |
| Output operation voltage (max) | 240 V | Certification | CE, EAC, EN 60950, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE, REACH, PEP, EOL |
| Automatic Voltage Regulation (AVR) | ✓ | Operational conditions | |
| Surge energy rating | 320 J | Operating temperature (T-T) | 0 - 40 °C |
| Hold time (min) | 4 ms | Storage temperature (T-T) | -15 - 45 °C |
| Hold time (max) | 8 ms | Operating relative humidity (H-H) | 0 - 95% |
| Efficiency | 98.9% | Storage relative humidity (H-H) | 0 - 95% |
| Noise level | 55 dB | Operating altitude | 0 - 3000 m |
| Audible alarm(s) | ✓ | Non-operating altitude | 0 - 15000 m |
| Auto-restart | ✓ | Technical details | |
| Ports & interfaces | | Sustainability certificates | Green Premium |
| AC outlet types | C13 coupler, C19 coupler | Compliance certificates | RoHS |
| Power plug | C20 coupler | Weight & dimensions | |
| AC outlets quantity | 9 AC outlet(s) | Width | 432 mm |
| Number of output IEC jumpers | 3 | Depth | 683 mm |
| USB port | ✓ | Height | 86 mm |
| Serial interface | ✓ | Weight | 44.3 kg |
| Serial interface type | RJ-45 | Package width | 600 mm |
| Ethernet LAN (RJ-45) ports | 1 | | |
| SmartSlot | ✓ | | |

| Battery | | Weight & dimensions | |
|----------------------------------|-------------------------|-----------------------------|-----------------------------|
| Battery technology | Sealed Lead Acid (VRLA) | Package depth | 980 mm |
| Battery capacity | 547 VAh | Package height | 254 mm |
| Typical backup time at full load | 3.2 min | Package weight | 51.7 kg |
| Typical backup time at half load | 11.5 min | Packaging data | |
| Battery life (max) | 5 year(s) | Rack mount kit | ✓ |
| Battery recharge time | 3 h | Cables included | RS-232, USB cable |
| Hot-swap battery | ✓ | Quick installation guide | ✓ |
| Automatic battery test | ✓ | Software CD | ✓ |
| | | Bundled software | Powershute Business Edition |
| | | Logistics data | |
| | | Harmonized System (HS) code | 85078000 |
| | | Other features | |
| | | Nominal output voltage | 230 V |
| | | Nominal input voltage | 230 V |



0731304337348



731304337348

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.