![APC logo]

APC Smart-UPS 2200VA LCD RM 2U 230V with SmartConnect UPS-virtalähde Linjainteraktiivinen 2,2 kVA 1980 W 9 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SMT2200RMI2UC

Tuotteen nimi : Smart-UPS 2200VA LCD RM 2U 230V with SmartConnect

APC Smart-UPS 2200VA LCD RM 2U 230V with SmartConnect. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 2,2 kVA, Lähtöteho: 1980 W. Ulostulojen määrä: 9 AC-pistorasia(a), USB-portin tyyppi: USB A-tyyppi, Sarjaliitännän tyyppi: RJ-45. Akkuteknologia: Sealed Lead Acid (VRLA), Akun kestoikä (maks.): 5 vuosi/vuosia, Akun latausaika: 3 h. Kotelo: Telineasennettava, Tuotteen väri: musta, Metallinen, Telineen kapasiteetti: 2U. Tuotteen leveys: 432 mm, Tuotteen syvyys: 683 mm, Tuotteen korkeus: 86 mm

Features

UPS topology *	Line-Interactive
Output power capacity *	2.2 kVA
Output power *	1980 W
Waveform *	Sine
Input operation voltage (min) *	151 V
Input operation voltage (max) *	302 V
Input frequency *	50/60 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Surge energy rating	375 J
Response time	6 ms
Output voltage Total Harmonic Distortion (THD)	5%
Noise level	55 dB
Power protection features	Over voltage
Audible alarm(s)	✔
Audible alarm modes	Alarm when on battery, Low battery alarm

Ports & interfaces

AC outlets quantity	9 AC outlet(s)
USB port	✔
USB 2.0 ports quantity	1
USB port type	USB Type-A
Serial interface	✔
Serial interface type	RJ-45
Ethernet LAN (RJ-45) ports	1
SmartSlot	✔

Battery

Battery technology	Sealed Lead Acid (VRLA)
Number of batteries supported	1
Battery life (max)	5 year(s)
Battery recharge time	3 h

Battery

Replacement battery cartridge	RBC43

Design

Form factor *	Rackmount
Rack capacity	2U
Cable length	2 m
Product colour *	Black, Metallic
Display type	LCD
Certification	CE, EAC, EN 60950, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Technical details

Sustainability certificates	Green Premium
Compliance certificates	RoHS

Weight & dimensions

Width	432 mm
Depth	683 mm
Height	86 mm
Weight	42.3 kg
Package width	600 mm
Package depth	980 mm
Package height	254 mm
Package weight	49.7 kg

Packaging data

Rack mount kit	✔
Cables included	RS-232, USB cable
Software CD	✔

Logistics data

Products per pallet	8 pc(s)
Harmonized System (HS) code	85078000

0731304337324

731304337324