

## Product Highlights

### Enjoy High-performance Wireless Connectivity

Harness the power of 802.11ac Wave 2 technology with MU-MIMO and experience wireless speeds of up to 1200 Mbps<sup>1</sup>

### Rugged Construction

IP68-compliant and designed to operate in harsh outdoor environments and temperatures ranging from -30 up to 60°C

### WiFi4EU Ready

Complies with Hotspot 2.0 (Wi-Fi CERTIFIED Passpoint®) with support for all the required IEEE standards



## DAP-3666

# Wireless AC1200 Wave 2 Dual-Band Outdoor PoE Access Point

## Features

### WiFi4EU Ready

- Wi-Fi CERTIFIED Passpoint® (complies with Hotspot 2.0)

### High-performance Connectivity

- IEEE 802.11ac Wave 2 wireless, Up to 1200 Mbps<sup>1</sup>
- MU-MIMO with beamforming
- Band steering
- Gigabit LAN port

### Made for Outdoor Environments

- IP68 water and dust-proof housing
- Weather resistant for temperatures between -30 and 60°C
- Gore-Tex® Technology repels liquid water while allowing for heat and humidity dissipation

### Centralised Management.

- Compatible with Nuclias Connect for centralised network management

### Trusted Security Features

- 128-bit personal wireless encryption
- 128-bit enterprise wireless encryption
- MAC address filtering
- Internal RADIUS server

### Convenient Installation

- Supports 802.3af Power over Ethernet
- Wall and pole mounting hardware included

The WiFi4EU ready DAP-3666 Wireless AC1200 Wave 2 Dual-Band Outdoor PoE Access Point is a versatile, high power outdoor access point designed with harsh weather resistant features making it an ideal solution for creating outdoor wireless hotspot networks. Utilising the cutting-edge speed of 802.11ac Wave 2, it delivers maximum combined wireless signal rates of up to 1200Mbps and supports MU-MIMO technology that allows multiple devices to get high-bandwidth Wi-Fi signal at the same time, distributing data more efficiently. It is Passpoint® certified by Wi-Fi Alliance and complies with Hotspot 2.0, making the process of devices finding and getting access to the known network seamless.

For centralise network management, administrators can use D-Link's free Nuclias Connect software or Nuclias Connect Hub (DNH-100) to configure and manage multiple access points. In addition to streamlining the management process, Nuclias Connect provides network administrators with the means to verify and conduct regular maintenance checks remotely, eliminating the need to send personnel out to physically verify proper operation.



Next Business Day Service

**Complimentary Next Business Day Service, as Standard**

Your network is the backbone of your business. Keeping it running is essential, even if the unexpected happens. D-Link Assist is a rapid-response technical support service that replaces faulty equipment quickly and efficiently. Maximising your uptime and giving you the confidence that instant support is only a phone call away.

All D-Link products with 5-year or Limited Lifetime warranty come with complimentary Next Business Day Service. D-Link will send out a replacement product to you on the next business day after acceptance of a product failure. On receipt of the replacement product, you simply arrange the return of the defective product to us. Any products with a 2-year/3-year warranty can also benefit from the Next Business Day advance replacement service when the optional 3-year warranty extension has been purchased.

[Find out more at eu.dlink.com/services](http://eu.dlink.com/services)

### Wireless AC1200 Wave 2 Dual-Band Outdoor PoE Access Point



Nuclias Connect is network management software that enables you to manage the network locally for dedicated privacy and security. It can be used either as an on-premises software management platform, or as a cloud solution hosted on a public cloud service.

Install the software on a local server on-site and manage up to 1,000 access points (APs), or optionally use the dedicated Nuclias Connect Hub which can manage up to 100 APs.

#### Flexibility to Meet Your Needs

Through software-based monitoring and remote management of all wireless APs on your network, Nuclias Connect offers tremendous flexibility compared to traditional hardware-based management systems. Configuration can be done remotely. Management software is customisable, and enables control and analytics of a broad or fine granularity, presentable in a variety of formats. Additionally, admins can provide and manage a variety of distributed deployments, including the option to configure settings and admin accounts in a specific manner for each deployment. Nuclias Connect gives you the financial and technical flexibility to expand from a small network to a larger one (up to 1,000 APs), while retaining a robust and centralised management system.









#### Insights at a Glance

Gain an extensive understanding of your network through usage analytics and status reports which can be viewed at a glance. Insights derived from traffic data can create business value. Traffic can be viewed across the entire network, to the level of a single AP.

#### Network Security & Data Privacy

Nuclias Connect balances the need for access convenience with the need for security. All communications over the system are encrypted, with your user data never leaving your possession. Additional security measures (such as firewalls) can also be added to your network, without undue technical difficulty.

#### Key Features

-  Free-to-Download Management Software
-  License-Free Centralised Management
-  Backwards-Compatibility
-  Intuitive Interface
-  Inexpensive Hardware Controller
-  Traffic Reporting & Analytics
-  Remote Config. & Batch Config.
-  Multi-Tenant & Role-Based Administration
-  Searchable Event Log and Change Log
-  Authentication via Customisable Captive Portal, 802.1x and RADIUS Server, POP3, LDAP, AD
-  Multilingual Support
-  Payment Gateway (Paypal) Integration and Front-Desk Ticket Management



## Wireless AC1200 Wave 2 Dual-Band Outdoor PoE Access Point

### Technical Specifications

#### General

Device Interfaces	<ul style="list-style-type: none"> <li>• 802.11a/b/g/n/ac wireless</li> </ul>	<ul style="list-style-type: none"> <li>• 2 Gigabit LAN Port (LAN1 supports PoE)</li> </ul>
LEDs	<ul style="list-style-type: none"> <li>• Power</li> </ul>	
Standards	<ul style="list-style-type: none"> <li>• IEEE 802.11a/b/g/n/ac</li> <li>• IEEE 802.3u/ab/af</li> <li>• IEEE 802.1x</li> </ul>	<ul style="list-style-type: none"> <li>• IEEE 802.11r</li> <li>• IEEE 802.11k</li> <li>• IEEE 802.11v</li> </ul>
Wireless Frequency Range	<ul style="list-style-type: none"> <li>• 2.4 GHz band: 2.4 GHz to 2.4835 GHz</li> </ul>	<ul style="list-style-type: none"> <li>• 5 GHz band: 5.15 to 5.35 GHz, 5.47 to 5.85 GHz<sup>2</sup></li> </ul>
Antennas	<ul style="list-style-type: none"> <li>• Two internal 6 dBi for 2.4 GHz</li> </ul>	<ul style="list-style-type: none"> <li>• Two internal 7 dBi for 5 GHz</li> </ul>
Maximum Output Power	<ul style="list-style-type: none"> <li>• 26 dbm for 2.4GHz</li> </ul>	<ul style="list-style-type: none"> <li>• 26 dbm for 5GHz</li> </ul>
Data Signal Rate <sup>1</sup>	<ul style="list-style-type: none"> <li>• 2.4 GHz</li> <li>• Up to 300 Mbps</li> </ul>	<ul style="list-style-type: none"> <li>• 5 GHz</li> <li>• Up to 867 Mbps</li> </ul>







#### Functionality

Security	<ul style="list-style-type: none"> <li>• 128-bit personal wireless encryption</li> <li>• 128-bit enterprise wireless encryption</li> <li>• WEP 64/128-bit encryption</li> <li>• SSID broadcast disable</li> </ul>	<ul style="list-style-type: none"> <li>• MAC address access control</li> <li>• Network Access Protection (NAP)</li> <li>• Internal RADIUS server</li> </ul>
Network Management	<ul style="list-style-type: none"> <li>• Telnet</li> <li>• Secure Telnet (SSH)</li> <li>• HTTP</li> <li>• Secure Socket Layer (SSL)</li> </ul>	<ul style="list-style-type: none"> <li>• Traffic control</li> <li>• Nuclias Connect Software</li> <li>• Nuclias Connect Hub</li> </ul>
Other Features	<ul style="list-style-type: none"> <li>• Fast Roaming Support with 802.11k, 802.11v, and 802.11r</li> </ul>	<ul style="list-style-type: none"> <li>• Passpoint Hotspot 2.0 Support</li> </ul>

#### Physical

Dimensions	<ul style="list-style-type: none"> <li>• 277 x 240 x 50 mm (10.91 x 9.45 x 1.97 inches)</li> </ul>
Weight	<ul style="list-style-type: none"> <li>• 981 grams (2.16 lbs) with antennas</li> </ul>
Operating Voltage	<ul style="list-style-type: none"> <li>• 48 V DC +/- 10%, or 802.3af PoE</li> </ul>
Maximum Power Consumption	<ul style="list-style-type: none"> <li>• 10.5 Watts</li> </ul>
Temperature	<ul style="list-style-type: none"> <li>• Operating: -30 to 60 °C (-22 to 140 °F)</li> <li>• Storage: -30 to 65 °C (-22 to 149 °F)</li> </ul>
Humidity	<ul style="list-style-type: none"> <li>• Operating: 10% to 90% non-condensing</li> <li>• Storage: 5% to 95% non-condensing</li> </ul>
Meantime Between Failure (MTBF)	<ul style="list-style-type: none"> <li>• &gt; 30,000 hours</li> </ul>

### Wireless AC1200 Wave 2 Dual-Band Outdoor PoE Access Point

<p>Certifications</p>	<ul style="list-style-type: none"> <li>• FCC</li> <li>• IC</li> <li>• CE</li> <li>• C-Tick</li> </ul>	<ul style="list-style-type: none"> <li>• UL</li> <li>• Wi-Fi® Certified</li> <li>• Wi-Fi Certified Passpoint®</li> <li>• IP68</li> </ul>
Antenna Pattern		
Orientation	H-Plane	E-Plane
<p>2.4 GHz Wall Mounted</p> 		
<p>5 GHz Wall Mounted</p> 		

## Wireless AC1200 Wave 2 Dual-Band Outdoor PoE Access Point

## Nuclias Connect Network Management Features

WLAN Management		
Maximum APs per Installation <sup>3</sup>	• 1,000 (large scale installations)	• 100 (small scale installations)
WLAN Management Features	<ul style="list-style-type: none"> <li>• AP grouping</li> <li>• Multi-tenancy</li> <li>• Visualized topology</li> <li>• NAT pass-through</li> </ul>	<ul style="list-style-type: none"> <li>• Setup wizard</li> <li>• AP discovery (layer 2 and layer 3)</li> <li>• Report system</li> </ul>
User Authentication		
Guest Portal	• Captive portal	
Authentication Method	<ul style="list-style-type: none"> <li>• Local</li> <li>• POP3</li> <li>• RADIUS</li> </ul>	<ul style="list-style-type: none"> <li>• LDAP</li> <li>• Voucher</li> </ul>
Hotspot Features	<ul style="list-style-type: none"> <li>• Built-in support for voucher-based authentication</li> <li>• Built-in hotspot manager for voucher creation and guest management</li> </ul>	• Rate limiting and bandwidth control for guest and hotspot portal
Wireless Features		
RF Management and Control	<ul style="list-style-type: none"> <li>• Auto Output Power Control</li> <li>• Auto Channel</li> </ul>	• Self-healing around failed APs
Multiple SSIDs per Radio(AP)	• 8	
Advanced Wireless Features	<ul style="list-style-type: none"> <li>• Band steering</li> <li>• L2 roaming</li> </ul>	<ul style="list-style-type: none"> <li>• Bandwidth optimisation</li> <li>• Airtime fairness</li> </ul>
System Management		
Management Interface	• Web-based user interface (HTTPS)	
Minimum System Requirements	• Computer running Microsoft Windows 10 or server 2016 (64 bit)	
Scheduling	• Firmware update	• Configuration update
Supported Devices		
Indoor Wireless N Access Points	• DAP-2230 (Single-Band N300, F/W ver. 2.0)	• DAP-2310 (Single-Band N300, F/W ver. 2.0)
Indoor Wireless AC Access Points	<ul style="list-style-type: none"> <li>• DAP-2360 (Single-Band N300, F/W ver. 2.0)</li> <li>• DAP-2610 (Dual-Band Wave 2 AC1300, F/W ver. 2.0)</li> <li>• DAP-2620 (Dual-Band Wave 2 AC1200, in-wall design)</li> <li>• DAP-2660 (Dual-Band AC1200, F/W ver. 2.0)</li> </ul>	<ul style="list-style-type: none"> <li>• DAP-2662 (Dual-Band Wave 2 AC1200, WiFi4EU-ready)</li> <li>• DAP-2680 (Dual-Band AC1200, F/W ver. 2.0)</li> <li>• DAP-2682 (Dual-Band Wave 2 AC2300)</li> <li>• DAP-2695 (Dual-Band AC1750, F/W ver. 2.0)</li> </ul>
Outdoor Access Points	<ul style="list-style-type: none"> <li>• DAP-3315 (Single-Band N300, F/W ver. 2.0)</li> <li>• DAP-3662 (Dual-Band AC1200, F/W ver. 2.0)</li> </ul>	• DAP-3666 (Dual-Band Wave 2 AC1200, WiFi4EU-ready)

<sup>1</sup> Maximum wireless signal rate derived from IEEE standard 802.11 and 802.11ac specifications. Actual data throughput will vary. Network conditions and environmental factors, including volume of network traffic, building materials and construction, and network overhead, lower actual data throughput rate. Environmental factors will adversely affect wireless signal range.

<sup>2</sup> Please note that operating frequency ranges vary depending on the regulations of individual countries and jurisdictions. The DAP-3662 may not support the 5.25-5.35 GHz and 5.47-5.725 GHz frequency ranges in certain regions. Compatibility with 802.11ac devices from other manufacturers is not guaranteed. All references to speed and range are for comparison purposes only. Product specifications, size, and shape are subject to change without notice, and actual product appearance may differ from that depicted herein.

<sup>3</sup> Number of wireless access points supported depends on the specification of the computer on which DNC is installed. To support 1000 APs, a computer with at least an Intel Core i7 with 16 GB RAM and 4 TB hard drive, and 20 Mbps uplink bandwidth is recommended. To support 100 APs, a computer with at least an Intel Core i5 3.2GHz with 8 GB RAM and 2 TB hard drive, and 10 Mbps uplink bandwidth is recommended.



For more information: [www.dlink.com](http://www.dlink.com)

**D-Link European Headquarters.** D-Link (Europe) Ltd., First Floor, Artemis Building, Odyssey Business Park, West End Road, South Ruislip HA4 6QE, United Kingdom. Specifications are subject to change without notice. D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries. All other trademarks belong to their respective owners. ©2019 D-Link Corporation. All rights reserved. E&OE.

Updated September 2019

**D-Link®**