

AXIS T94C01L Recessed Mount

Discreet and elegant installation in drop ceilings

AXIS T94C01L Recessed Mount is an indoor mount for drop ceiling installations. It comes with a single-screw ceiling attachment for quick and easy installation. AXIS T94C01L Recessed Mount enables sleek, elegant and discreet recessed ceiling installations of Axis indoor cameras, compatible with AXIS M42 series and AXIS Companion Dome mini LE. It features a patent-pending single-screw ceiling attachment design, which makes the installation quick and easy without having to remove the ceiling tile. Axis fixed dome camera attached to the recessed mount is embedded into the ceiling, revealing only the camera dome and the low-profile cover ring.

- > [Quick and easy installation in drop ceilings](#)
- > [Elegant and discreet recessed ceiling installations](#)
- > [Compatible with AXIS M42 series as well as AXIS Companion Dome mini LE](#)



AXIS T94C01L Recessed Mount

General	
Supported products	AXIS M42-V/-LV Series AXIS Companion Dome mini LE
Casing	Material: 54% recycled plastic Color: white NCS S 1002-B
Sustainability	PVC free
Mounting	Recessed in drop ceilings
Environment	Indoor
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Approvals	Safety IEC/EN/UL 62368-1 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-78, IEC/EN 62262 IK08
Dimensions	Outer dimensions Length: 252 mm (9.9 in), Height: 140 mm (5.5 in)
	Maximum height inside ceiling 127 mm (5 in) Tile thickness 1–60 mm (0.04–2.36 in) Cover ring ø 152 mm (6 in) Cut-out in ceiling ø 131 mm (6 3/16 in)
	Weight 260 g (0.57 lb)
	Maximum load 600 g (1.32 lb)
	Cable routing Top: cable hole
	Included accessories Installation guide, gasket
	Optional accessories AXIS Safety Wire 3 m
	Warranty 3-year warranty, see axis.com/warranty

Environmental responsibility:

axis.com/environmental-responsibility