

D-Link DBA-1210P WLAN-tukiasema 1200 Mbit/s Valkoinen Power over Ethernet -tuki

Tuotemerkki : D-Link

Tuotekoodi: DBA-1210P

Tuotteen nimi : DBA-1210P

D-Link DBA-1210P. 2,4 GHz, 5 GHz, Tiedonsiirron enimmäisnopeus: 1200 Mbit/s. Tietoturva-algoritmit: 64-bit WEP, 128-bit WEP, WPA-Enterprise, WPA-PSK, WPA2-Enterprise, WPA2-PSK. Ethernet LAN - datanopeudet: 10,100,1000 Mbit/s. Power over Ethernet -tuki. Tuotteen väri: Valkoinen



Features		Technical details	
2.4 GHz *	✓	Products per shipping (inner) case	5 pc(s)
5 GHz *	✓	Pallet gross weight (air)	397.7 kg
6 GHz *	✗	Master (outer) cases per pallet (air)	96 pc(s)
Maximum data transfer rate *	1200 Mbit/s	Products per pallet (air)	480 pc(s)
Maximum data transfer rate (2.4 GHz)	300 Mbit/s	Pallet gross length	110 cm
Maximum data transfer rate (5 GHz)	867 Mbit/s	Pallet gross width	120 cm
Ethernet LAN data rates	10,100,1000 Mbit/s	Pallet height (air)	2.05 m
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x	Pallet gross weight (sea)	397.7 kg
		Master (outer) cases per pallet (sea)	96 pc(s)
		Products per pallet (sea)	480 pc(s)
		Pallet height (sea)	2.05 m
MIMO	✓	Shipping (inner) case gross weight	3.83 kg
Flow control support	✓	Certificates	
Mean time between failures (MTBF)	30000 h	Certification	FCC Class B CE Class B UL IC Class B
Security		Weight & dimensions	
Security algorithms *	64-bit WEP, 128-bit WEP, WPA-Enterprise, WPA-PSK, WPA2-Enterprise, WPA2-PSK	Width	170 mm
Ports & interfaces	Ethernet LAN (RJ-45) ports * 1	Depth	170 mm
		Height	28 mm
		Packaging data	
Package width	205 mm		
Package depth	274 mm		
Package height	65 mm		
Package weight	526.5 g		
Power		Operational conditions	
Power over Ethernet (PoE) *	✓	Operating relative humidity (H-H)	10 - 90%
AC input voltage	100 - 240 V	Operating temperature (T-T)	0 - 40 °C
AC input frequency	50 - 60 Hz		
Output voltage	12 V		
Output current	1 A		

Design		Operational conditions	
Product colour *	White	Storage temperature (T-T)	-20 - 65 °C
LED indicators	✓	Storage relative humidity (H-H)	5 - 95%
Internal	✗	Logistics data	
Technical details		Harmonized System (HS) code	85176990
Shipping (inner) case length	35.2 cm		
Shipping (inner) case width	29 cm		
Shipping (inner) case height	23.9 cm		
Shipping (inner) case net weight	2.1 kg		



0790069432699



790069432699



0790069444326



790069444326

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.