![Lenovo]

Lenovo ThinkPad USB-C Dock Gen 2 Langallinen USB 3.2 Gen 1 (3.1 Gen 1) Type-C musta

Tuotemerkki : Lenovo

Tuotekoodi: 40AS0090UK

Tuotteen nimi : ThinkPad USB-C Dock Gen 2

Lenovo ThinkPad USB-C Dock Gen 2. Yhteysteknologia: Langallinen, Isäntäkoneen käyttöliittymä: USB 3.2 Gen 1 (3.1 Gen 1) Type-C, Kuulokkeiden liitettävyys: 3,5 mm. Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s. Tuotteen väri: musta, Tiedonsiirtonopeus: 10 Gbit/s, HD-tyyppi: 4K Ultra HD. Virtalähteen malli: DC, AC-syöttöjännite: 100 - 240 V, AC-syöttötaajuus: 50 - 60 Hz. Windows-käyttöjärjestelmätuki: Windows 10, Windows 7

Ports & interfaces

Connectivity technology *	Wired
Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-C
USB 2.0 ports quantity *	2
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	3
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	1
HDMI ports quantity *	1
HDMI version	2.0
DisplayPorts quantity	2
Microphone in *	✘
Combo headphone/mic port	✔
Headphone connectivity	3.5 mm

Network

Ethernet LAN *	✔
Ethernet LAN (RJ-45) ports	1
Ethernet LAN data rates	10,100,1000 Mbit/s
Wake-on-LAN ready	✔

Performance

Card reader integrated *	✘
Data transfer rate	10 Gbit/s
HD type	4K Ultra HD
Maximum digital resolution	3840 x 2160 pixels
Number of displays supported	3
Cable lock slot	✔
Product colour *	Black
Plug and Play	✔
Brand compatibility	Lenovo

Performance

Compatibility	ThinkPad T490 (20N2, 20N3, 20Q9, 20QH), ThinkPad T590 (20N4, 20N5), ThinkPad X280 (20KE,20KF), ThinkPad T480 (20L5,20L6), ThinkPad X1 Carbon 6th (20KH, 20KG), ThinkPad X270 (20HM, 20HN, 20K5, 20K6), ThinkPad T480s (20L7,20L8)
Certification	FCC/ICES, CE, KCC, RCM, BSMI, VCCI, CB, cULus, EAC, TUV- Mark, Serbia Kvalitet, LoA, Israel SII, Ukraine DoC, NOM

Power

Power source type	DC
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power supply	90 W

Software

Windows operating systems supported	Windows 10, Windows 7

Operational conditions

Operating temperature (T-T)	0 - 35 °C
Operating relative humidity (H-H)	20 - 95%

Weight & dimensions

Width	171 mm
Depth	80 mm
Height	30.8 mm
Weight	325 g

Packaging data

Quantity per pack	1 pc(s)
Package width	210 mm
Package depth	158 mm
Package height	75 mm
Package weight	960 g

Packaging content

Cables included	AC, USB Type-C
AC adapter included	✔
Manual	✔

Logistics data

Harmonized System (HS) code	84733020

0193124916392

193124916392