Lexmark MS622de 1200 x 1200 DPI A4

Brand: Lexmark Product code: 36S0507

Product name: MS622de

Lexmark MS622de. Print technology: Laser. Number of print cartridges: 1, Maximum duty cycle: 175000 pages per month. Maximum resolution: 1200 x 1200 DPI. Maximum ISO A-series paper size: A4. Print speed (black, normal quality, A4/US Letter): 47 ppm, Duplex printing. Product colour: Black, Grey





Printing		Performance	
Colour *	×	Sound pressure level (printing)	56 dB
Print technology * Duplex printing *	Laser 🗸	Sound pressure level (duplex printing)	56 dB
Maximum resolution *	1200 x 1200 DPI	Noise level (ready)	14 dB
Print speed (black, normal quality, A4/US Letter) *	47 ppm	Design	
Duplex print speed (black, normal	24 nnm	Product colour *	Black, Grey
quality, A4/US Letter)	24 ppm	Built-in display *	√
Time to first page (black, normal)	6 s	Colour display Display diagonal	10.9 cm (4.3")
Features		Touchscreen	10.9 cm (4.5) ✓
Maximum duty cycle *	175000 pages per month	Control type	Touch
Recommended duty cycle Printing colours * Number of print cartridges *	2000 - 20000 pages per month Black 1	os.iii v. type	ENERGY STAR, ICES-003 Class B, BSMI Class B, VCCI Class B, US FDA, UL 60950-1, FCC Class B, CUL CAN / CSA-C22.2 60950-1, NOM, CB EN /
Page description languages *	Microsoft XPS, PCL 5e, PDF 1.7, PPDS, PostScript 3		IEC 60950-1, CB EN / IEC 60825-1, CE DoC (EN 62301 Class B, EN
Country of origin	China	Certification	62311, CE EN / IEC 60950-1, CE EN /
Input & output capacity			IEC 60825-1, EN 61000-3, EN 55022 Class B, EuP, EN 55024 , UL), EFTA
Total number of input trays * Total input capacity * Total output capacity *	2 650 sheets 250 sheets		(CE), KCC, CCC, CECP, CEL, C-tick DoC, UL-AR, KC mark, UL GS mark, EC1275, MET-I, ISO 532B, ECMA-370, TED, GOST -R, SII, TER
Maximum number of input trays	5	Power	
Maximum input capacity Maximum output capacity	2300 sheets 250 sheets	Power consumption (printing) *	670 W
Paper handling		Power consumption (ready)	9.5 W
Maximum ISO A-series paper size *	A4	Power consumption (standby) Power consumption (off)	2.2 W 0.1 W
	Card stock, Envelopes, Labels, Plain	Energy Star Typical Electricity	
Paper tray media types *	paper, Transparencies	Consumption (TEC)	2.1 kWh/week
ISO A-series sizes (A0A9) *	A4, A5, A6	System requirements	
Non-ISO print media sizes	Executive, Folio, Legal, Letter, Oficio, Statement, Universal	Windows operating systems supported	✓
JIS B-series sizes (B0B9)	B5	Mac operating systems supported	1
Envelopes sizes	7 3/4, 9, 10, DL	Linux operating systems supported	✓
Paper tray media weight Multi-Purpose Tray media weight	60 - 120 g/m² 60 - 216 g/m²	Other operating systems supported	✓
, , ,	50 210 g/m	Operational conditions	
Ports & interfaces	File and HCD 2.0	Operating temperature (T-T)	10 - 32 °C
Standard interfaces	Ethernet, USB 2.0	Operating relative humidity (H-H)	8 - 80%
USB 2.0 ports quantity USB connector	3 USB Type-A / USB Type-B	Operating altitude	0 - 5000 m
Optional connectivity	Wireless LAN	Sustainability	
		Sustainability certificates	ENERGY STAR

Network		Weight & dimensions	
Wi-Fi *	×	Width	399 mm
Ethernet LAN *	✓	Depth	374 mm
Cabling technology	10/100/1000Base-T(X)	Height	303 mm
Ethernet LAN data rates	10,100,1000 Mbit/s	Weight	16.1 kg
Security algorithms	HTTPS, IPSec, LEAP, MD5, MSCHAPv2, PEAP, SNMPv3, SSL/TLS, TTLS	Packaging data	
		Package width	430 mm
Supported network protocols (IPv4)	UDP	Package depth	470 mm
		Package height	422 mm
Supported network protocols (IPv6)	TCP / IP IPv6	Package weight	18.1 kg
Management protocols	DHCP, APIPA (AutoIP), mDNS, IGMP, Bonjour, WINS, DDNS, SNMPv3, SNMPv1, SNMPv2c, Telnet, NTP, ICMP, HTTP, DNS, ARP, HTTPs (SSL /TLS), Finger	Packaging content	
		Cartridge(s) included Included cartridge capacity (black)	√ 6000 pages
Mobile printing technologies	Apple AirPrint	Manual	✓
Performance		Software CD	✓
Internal memory *	1024 MB	Documentation CD	V
Maximum internal memory	1024 MB	Cables included	AC
•	1024 MB		
Card reader integrated	4		
Built-in processor	1000 1111		
Processor frequency	1000 MHz		
Processor cores	2		





734646659499

0734646659499

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.