

Lexmark CS331dw Colour 600 x 600 DPI A4 Wi-Fi

Brand : Lexmark

Product code: 40N9121

Product name : CS331dw

Lexmark CS331dw. Print technology: Laser, Colour. Number of print cartridges: 4, Maximum duty cycle: 50000 pages per month. Maximum resolution: 600 x 600 DPI. Maximum ISO A-series paper size: A4. Print speed (black, normal quality, A4/US Letter): 24 ppm, Duplex printing. Display: LCD. Network ready, Wi-Fi. Product colour: Black, White



Printing		Network	
Print speed (colour, normal quality, A4/US Letter)	24 ppm	Supported network protocols (IPv6)	TCP / IP, TCP, UDP
Colour *	✓		DHCP, APIPA (AutoIP), BOOTP, RARP, mDNS, IGMP, WINS, DDNS, SNMPv3, SNMPv1, SNMPv2c, NTP, ICMP, HTTP, DNS, ARP, HTTPs (SSL / TLS), Finger
Print technology *	Laser	Management protocols	
Duplex printing *	✓		
Maximum resolution *	600 x 600 DPI		
Print speed (black, normal quality, A4/US Letter) *	24 ppm		
Duplex print speed (black, normal quality, A4/US Letter)	13 ppm		
Duplex print speed (colour, normal quality, A4/US Letter)	13 ppm		
Time to first page (black, normal)	10.9 s		
Time to first page (colour, normal)	10.9 s		
Print margins (top, bottom, right, left)	4.2 mm		
Features		Performance	
Maximum duty cycle *	50000 pages per month	Internal memory *	512 MB
Recommended duty cycle	600 - 2500 pages per month	Maximum internal memory	512 MB
Printing colours *	Black, Cyan, Magenta, Yellow	Built-in processor	✓
Number of print cartridges *	4	Processor frequency	1000 MHz
Page description languages *	PCL 5, PCL 6, PCLm, PostScript 3	Processor cores	2
Average cartridge yield (black)	750 pages	Sound pressure level (printing)	52 dB
Average cartridge yield (CMY)	500 pages	Sound pressure level (duplex printing)	51 dB
		Sound power level (standby)	14 dB
Input & output capacity		Design	
Total number of input trays *	2	Market positioning *	Business
Total input capacity *	251 sheets	Product colour *	Black, White
Total output capacity *	100 sheets	Built-in display *	✓
Paper input type	Paper tray	Display	LCD
Maximum number of input trays	2		RAL-UZ-205, ICES-003 B, US FDA / CDRH, UL 60950-1, FCC Class B, cUL CAN / CSA-C22.2 60950-1, CB EN / IEC 60950-1, CB EN / IEC 60825-1, CE DoC (EN 62311, EN 55022 (B), EN 55024, EN 61000, EN 61000, UL), EFTA (CE), KCC, CCC, CECP, CEL, RCM DoC, UL-AR, KC, UL GS, UCRF, BSMI EMC B
Maximum input capacity	251 sheets	Certification	
Maximum output capacity	100 sheets		
Paper handling		Power	
Maximum ISO A-series paper size *	A4	Power consumption (printing) *	395 W
Paper tray media types *	Card stock, Envelopes, Glossy paper, Labels, Plain paper	Power consumption (standby)	0.9 W
ISO A-series sizes (A0...A9) *	A4, A5, A6	Power consumption (PowerSave)	17 W
ISO B-series sizes (B0...B9)	B5	Energy Star Typical Electricity Consumption (TEC)	0.31 kWh/week
ISO C-series sizes (C0...C9)	C5		
Non-ISO print media sizes	Executive, Folio, Hagaki card, Legal, Letter, Oficio, Statement, Universal		
Envelopes sizes	7 3/4, 9, 10, B5, C5, DL		
		System requirements	
		Windows operating systems supported	Windows 10, Windows 7, Windows 8
		Linux operating systems supported	SUSE Linux Enterprise Desktop 10, SUSE Linux Enterprise Desktop 11, SUSE Linux Enterprise Desktop 12, Ubuntu 16.04, openSUSE 42.3

Paper handling		System requirements	
Paper tray media weight	60 - 176 g/m ²	Server operating systems supported	Windows 2000 Server, Windows Server 2003, Windows Server 2003 x64, Windows Server 2016
Ports & interfaces		Operational conditions	
USB port *	✓	Operating temperature (T-T)	10 - 32 °C
USB 2.0 ports quantity	1	Operating relative humidity (H-H)	8 - 80%
USB connector	USB Type-B	Operating altitude	0 - 3048 m
Network		Sustainability	
Network ready	✓	Sustainability certificates	Blue Angel, EPEAT Silver, ENERGY STAR
Wi-Fi *	✓	Weight & dimensions	
Ethernet LAN *	✓	Width	411.2 mm
Cabling technology	10/100/1000Base-T(X)	Depth	394.1 mm
Ethernet LAN data rates	10,100,1000 Mbit/s	Height	243.7 mm
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)	Weight	16.1 kg
Security algorithms	HTTPS, IPSec, SNMP, SNMPv3, SSL/TLS	Packaging data	
Supported network protocols (IPv4)	TCP / IP, TCP, UDP	Package width	332 mm
		Package depth	556 mm
		Package height	519 mm
		Package weight	19.1 kg
		Packaging content	
		Cartridge(s) included	✓
		Included cartridge capacity (black)	750 pages
		Included cartridge capacity (CMY)	500 pages
		Quick start guide	✓
		Cables included	AC

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-NOV-2024. Prints or copies of Information are only valid on the printed Publication date