



## APC Easy UPS SMV UPS-virtalähde Linjainteraktiivinen 2 kVA 1400 W 6 AC-pistorasia(a)

**Tuotemerkki :** APC

**Tuotekoodi:** SMV2000CAI

**Tuotteen nimi :** Easy UPS SMV

APC Easy UPS SMV. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 2 kVA, Lähtöteho: 1400 W. Pistorasian tyypit: IEC 320, Ulostulojen määrä: 6 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 7 ah, Akun jännite: 12 V. Kotelo: Tower, Tuotteen väri: musta, Näytön tyyppi: LCD. Tuotteen leveys: 180 mm, Tuotteen syvyys: 455 mm, Tuotteen korkeus: 240 mm



Features		Battery	
UPS topology *	Line-Interactive	Number of batteries supported	4
Output power capacity *	2 kVA	Battery life (max)	5 year(s)
Output power *	1400 W	Battery recharge time	4 h
Waveform *	Sine	Cold start	✓
Input operation voltage (min) *	157 V		
Input operation voltage (max) *	303 V		
Input frequency *	45/65 Hz		
Output operation voltage (min)	230 V		
Output operation voltage (max)	230 V		
Output frequency	50/60 Hz		
Output voltage regulation	-1 - 1%		
Automatic Voltage Regulation (AVR)	✓		
Maximum current	20 A		
Crest factor	3:1		
Noise level	45 dB		
Power protection features	Overload, Short circuit		
Audible alarm(s)	✓		
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm		
Ports & interfaces		Design	
AC outlet types	IEC 320	Form factor *	Tower
AC outlets quantity	6 AC outlet(s)	Product colour *	Black
USB port	✓	Display type	LCD
		LED indicators	✓
		International Protection (IP) code	IP20
Battery		Operational conditions	
Battery technology	Sealed Lead Acid (VRLA)	Operating temperature (T-T)	0 - 40 °C
Battery capacity	7 Ah	Storage temperature (T-T)	-10 - 40 °C
Battery voltage	12 V	Operating relative humidity (H-H)	0 - 95%
		Storage relative humidity (H-H)	0 - 95%
		Operating altitude	0 - 3000 m
		Weight & dimensions	
		Width	180 mm
		Depth	455 mm
		Height	240 mm
		Weight	23.5 kg
		Battery width	32.6 cm
		Battery depth	60.1 cm
		Battery height	41 cm
		Battery weight	26.9 kg
		Packaging data	
		Cables included	USB cable
		Manual	✓

**Logistics data**

Harmonized System (HS) code 85078000



0731304346548



731304346548

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.