tp-link

TP-Link Archer T2U V3 WLAN 433 Mbit/s

Tuotemerkki : TP-Link   **Tuotekoodi:** ARCHER T2U V3

Tuotteen nimi : Archer T2U V3

TP-Link Archer T2U V3. Yhteysteknologia: Langaton, Isäntäkoneen käyttöliittymä: USB, Käyttöliittymä: WLAN. Tiedonsiirron enimmäisnopeus: 433 Mbit/s, Wi-Fi-standardi: Wi-Fi 5 (802.11ac), Wi-Fi-taajuus: Kaksitaajuus (2,4 GHz/5 GHz). Tuotteen väri: musta

Ports & interfaces

Connectivity technology *	Wireless
Host interface *	USB
Interface *	WLAN
USB version	2.0

Network

Maximum data transfer rate *	433 Mbit/s
Networking standards *	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3ac
Wi-Fi	✔
Wi-Fi band	Dual-band (2.4 GHz / 5 GHz)
Frequency range	2.4 - 5 GHz
Top Wi-Fi standard	Wi-Fi 5 (802.11ac)
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
WLAN data transfer rates supported	11,54,150,433 Mbit/s
Modulation	16-QAM, 64-QAM, 256-QAM, CCK, DBPSK, DQPSK, OFDM
Security algorithms	WEP, WPA, WPA-PSK, WPA2, WPA2-PSK

Design

Component for *	PC/Laptop
Product colour	Black
Internal *	✘
Antenna	✔
LED indicators	Status

Design

Receiver sensitivity	11a 6Mbps: -94dBm 11a 54Mbps: -78dBm 11n HT20 MCS0: -94dBm 11n HT20 MCS7: -77dBm 11n HT40 MCS0: -92dBm 11n HT40 MCS7: -74dBm 11ac VHT80 MCS0: -89dBm 11ac VHT80 MCS9: -64dBm 11b 1Mbps: -99dBm 11b 11Mbps: -91dBm 11g 6Mbps: -94dBm 11g 54Mbps: -77dBm 11n HT20 MCS0: -95dBm 11n HT20 MCS7: -76dBm 11n HT40 MCS0: -92dBm 11n HT40 MCS7: -73dBm
Certification	CE, FCC

System requirements

Windows operating systems supported	Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%

Weight & dimensions

Width	40.5 mm
Depth	19.7 mm
Height	10.3 mm

Technical details

Compliance certificates	RoHS

Logistics data

Harmonized System (HS) code	85176990

Other features

Housing material	Plastic
Quick start guide	✔

8459730508560

0845973050856

845973050856

8592978172893