

AXIS P1377-LE Network Camera

Fully-equipped 5 MP surveillance for the great outdoors

With a robust design, AXIS P1377-LE offers excellent 5 MP video and can withstand extreme temperatures ranging from -40 °C to 60 °C (-40 °F to 140 °F). For extra protection an optional weathershield is available. It delivers great details in challenging or low light and includes Axis OptimizedIR for surveillance in pitch darkness. Designed as a deterrent, it includes electronic image stabilization, shock detection, tampering alarm and video streaming indicator. Axis Zipstream supporting H.264/H.265 provides exceptional savings on bandwidth and storage. Plus, with CS mount and support for motorized i-CS, you can easily change lens to meet your requirements.

- > 30 fps in 5 MP or up to 180 fps in HDTV 720p
- > OptimizedIR and Forensic WDR
- > Signed firmware and secure boot
- > Electronic image stabilization
- > Zipstream supporting H.264 and H.265



AXIS P1377-LE Network Camera

Camera		System integration	
Image sensor	1/2.7" progressive scan RGB CMOS	Application Programming Interface	Open API for software integration, including VAPIX® and AXIS Camera Application Platform, specifications at axis.com AXIS Video Hosting System (AVHS) with One-Click Connection One-click cloud connection ONVIF® Profile G, ONVIF® Profile M, ONVIF® Profile S and ONVIF® Profile T, specification at onvif.org
Lens	IR corrected, CS-mount lens, P-Iris Varifocal 2.8–8 mm, F1.2 Horizontal field of view: 90°–38° Vertical field of view: 67°–28°	Onscreen controls	Electronic image stabilization Day/night shift Defogging Wide dynamic range
Day and night	Automatically removable infrared-cut filter	Event triggers	Analytics, shock detection, open casing, edge storage events, supervised external input, audio level, time scheduled MQTT subscribe
Minimum illumination	5 MP 25/30 fps with Forensic WDR and Lightfinder: Color: 0.13 lux, at 50 IRE F1.2 B/W: 0.03 lux, at 50 IRE F1.2 0 lux with IR illumination on	Event actions	File upload: FTP, SFTP, HTTP, HTTPS, network share and email Notification: email, HTTP, HTTPS and TCP External output activation Video recording to edge storage, Play audio clip Pre- and post-alarm video buffering PTZ preset, Guard tour, Overlay text Day/Night switching, Status LED activation MQTT publish Send SNMP trap
Shutter speed	WDR: 1/33500 s to 1/5 s No WDR: 1/50000 s to 1/5 s	Built-in installation aids	Focus assistant, pixel counter, remote back focus, autorotation, remote focus and zoom and with optional i-CS lens.
System on chip (SoC)		Analytics	
Model	ARTPEC-7	AXIS Object Analytics	Object classes: humans, vehicles Trigger conditions: line crossing, object in area, time in area ^{BETA} Up to 10 scenarios Metadata visualized with trajectories and color-coded bounding boxes Polygon include/exclude areas Perspective configuration ONVIF Motion Alarm event
Memory	1 GB RAM, 512 MB Flash	Metadata	Object data: Classes: humans, faces, vehicles, license plates Confidence, position Event data: Producer reference, scenarios, trigger conditions
Compute capabilities	Machine learning processing unit (MLPU)	Applications	Included AXIS Object Analytics, AXIS Video Motion Detection, AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard, active tampering alarm, audio detection Supported AXIS Live Privacy Shield, AXIS Perimeter Defender Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap
Video		Cybersecurity	
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Motion JPEG Controllable frame rate and bandwidth	Edge security	Software: Signed firmware, brute force delay protection, digest authentication, password protection, AES-XTS-Plain64 256bit SD card encryption Hardware: Secure boot
Resolution	2592x1944 (5 MP) to 160x90 2688x1512 (4 MP) to 160x90 1920x1080 (HDTV 1080p) to 160x90 1280x720 (HDTV 720p) to 160x90	Network security	IEEE 802.1X (EAP-TLS) ^a , HTTPS/HSTS ^a , TLS v1.2/v1.3 ^a , Network Time Security (NTS), X.509 Certificate PKI, IP address filtering
Frame rate	Capture mode 5 MP: 25/30 fps (50/60 Hz) Capture mode 4 MP: 25/30 fps (50/60 Hz) Capture mode HDTV 720p: 180 fps	Documentation	<i>AXIS OS Hardening Guide</i> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> AXIS OS Software Bill of Material (SBOM) To download documents, go to axis.com/support/cybersecurity/resources To read more about Axis cybersecurity support, go to axis.com/cybersecurity
Video streaming	Multiple, individually configurable streams in H.264, H.265, and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 Low latency mode Video streaming indicator	General	
Multi-view streaming	Up to 8 individually cropped out view areas	Casing	IP66-, IP67- and NEMA 4X-rated, IK10 impact-resistant polymer enclosure with aluminium base and intrusion alarm switch Weathershield with black anti-glare coating Color: White NCS S 1002-B
Image settings	Saturation, contrast, brightness, sharpness, Forensic WDR: Up to 120 dB depending on scene, white balance, day/night threshold, exposure mode, exposure zones, local contrast, tone mapping, compression, orientation: auto, 0°, 90°, 180°, 270° including Corridor Format, mirroring of images, dynamic text and image overlay, privacy masks, defogging, electronic image stabilization, barrel distortion correction, scene profiles: forensic, vivid, traffic overview	Sustainability	PVC free
Pan/Tilt/Zoom	Digital PTZ Uploadable PTZ driver (Pelco D pre-installed)	Power	Without front heater 12–28 V DC, max 19.1 W, typical 10.5 W Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 2 Class 4, max 20.4 W, typical 11.1 W
Audio			
Audio streaming	Two-way, full duplex		
Audio encoding	AAC LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz, LPCM 8/16/32/48 kHz Configurable bit rate		
Audio input/output	External microphone input, line input, digital input with ring power, line output, automatic gain control		
Network			
Security	IP address filtering, HTTPS ^a encryption, IEEE 802.1X (EAP-TLS) ^a network access control, user access log, centralized certificate management		
Network protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS ^a , HTTP/2, TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SFTP, SRTP/RTSPS, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SSH, LLDP, CDP, MQTT v3.1.1, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf)		

	With disabled IR: Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3, max 12.95 W, typical 6.7 W Power redundancy	IEC/EN/UL 62368-1, CAN/CSA C22.2 No. 62368-1, IEC/EN/UL 60950-22, CAN/CSA-C22.2 No. 60950-22, IEC 62471, IS 13252
Power	With front heater 12–28 V DC, max 25.5 W, typical 10.5 W Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 2 Class 4, max 25.5 W, typical 11.1 W With disabled IR: Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3, max 25.5 W, typical 6.7 W Power redundancy	Environment IEC/EN 60529 IP66/IP67, NEMA 250 Type 4X, NEMA TS 2 (2.2.7–2.2.9), IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 62262 IK10 Network NIST SP500–267
Connectors	RJ45 10BASE-T/100BASE-TX/1000BASE-T I/O: 6-pin 2.5 mm terminal block, for 2 supervised alarm inputs and 2 outputs RS485/RS422, 2 pcs, 2 pos, full duplex, terminal block DC input, terminal block 3.5 mm mic/line in, 3.5 mm line out i-CS connector (compatible with P-Iris and DC-iris)	Dimensions 404 x 159 x 168 mm (15.9 x 6.3 x 6.6 in) Weight 2.4 kg (5.3 lb)
IR illumination	OptimizedIR with power-efficient, long-life 850 nm IR LEDs Range 50 m (164 ft) or more, depending on the scene	Included accessories Installation guide, Windows® decoder 1-user license, wall mount bracket, sunshield, connector kit IK10 tool Torx® T20 screw driver, Torx® T30 screw bit AXIS P13 Weathershield Kit A Pre-mounted AXIS Fixed Box IR Illuminator Kit A
Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com	Optional lenses Lens Computar i-CS 2.8–8.5 mm Lens CS 4–10 mm F0.9 P-Iris Lens i-CS 9–50 mm F1.5 8 MP Tamron 5MP Lens P-Iris 8–50 mm F1.6 Theia Varifocal Ultra Wide Lens 1.8–3.0 mm
Operating conditions	–40 °C to 60 °C (–40 °F to 140 °F) Maximum temperature according to NEMA TS 2 (2.2.7): 74 °C (165 °F) Humidity 10–100% RH (condensing) Wind load (sustained): 55 m/s (123 mph)	Optional accessories Axis mounts, Axis lenses, Axis midspans, Axis microphones AXIS P13 Weathershield Extension A AXIS T8355 Digital Microphone AXIS T99A10 Positioning Unit 24 V AC/DC For more accessories, see axis.com
Storage conditions	–40 °C to 65 °C (–40 °F to 149 °F) Humidity 5–95% RH (non-condensing)	Video management software AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available at axis.com/vms
Approvals	EMC EN 55032 Class A, EN 50121-4, IEC 62236-4, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KCC KN32 Class A, KN35 Safety	Languages English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese Warranty 5-year warranty, see axis.com/warranty

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (openssl.org/), and cryptographic software written by Eric Young (eyay@cryptsoft.com).