

D-Link DGS-1250-52X verkkokytkin Hallittu L3 Gigabit Ethernet (10/100/1000) musta

Tuotemerkki : D-Link

Tuotekoodi: DGS-1250-52X

Tuotteen nimi : DGS-1250-52X



D-Link DGS-1250-52X. Kytin tyyppi: Hallittu, Kytinkerros: L3. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 48, Console-portti: RJ-45. MAC-osoitetaulukko: 32000 entries, Kytkentäkapasiteetti: 176 Gbit/s. Verkkostandardit: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE....
Telineasennus

Management features		Design	
Switch type *	Managed	Electromagnetic compatibility	CE A, VCCI A, FCC A, IC, BSMI
Switch layer	L3	Performance	
Quality of Service (QoS) support	✓	Memory type	DDR3-SDRAM
Web-based management	✓	Internal memory	2048 MB
ARP inspection	✓	Flash memory	64 MB
Configuring Location Settings (CLI)	✓	Noise level	50.7 dB
System event log	✓	Mean time between failures (MTBF)	589984.72 h
MIB support	RFC2893, RFC4213, RFC4291, RFC2464, RFC2462, RFC4862, RFC2461, RFC4861, RFC2573, RFC1321, RFC2284, RFC2865, RFC2716, RFC3580, RFC826, RFC2463, RFC4443, RFC792, RFC793, RFC768, RFC791, RFC2389, RFC4113, RFC4022, RFC2618, RFC2674, RFC1398, RFC1643, RFC1650, RFC2358, RFC2665, RFC2021, RFC271, RFC1757, RFC2819, RFC1442, RFC1901, RFC1902, RFC1903, RFC1904, RFC1905, RFC1906, RFC1907, RFC1908, RFC2578, RFC3418, RFC2573, RFC2575, RFC2576, RFC1212, RFC1213, RFC1215, RFC1493, RFC1157, RFC2620,	Power	
		Power supply included *	✓
		AC input voltage	100 - 240 V
		AC input frequency	50 - 60 Hz
		Power consumption (max)	51.2 W
		Power over Ethernet (PoE)	
		Power over Ethernet (PoE) *	✗
		Operational conditions	
		Operating temperature (T-T)	-5 - 50 °C
		Storage temperature (T-T)	-20 - 70 °C
		Operating relative humidity (H-H)	0 - 95%
		Storage relative humidity (H-H)	0 - 95%
		Heat dissipation	174.592 BTU/h
Ports & interfaces		Weight & dimensions	
Basic switching RJ-45 Ethernet ports quantity *	48	Width	440 mm
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Depth	210 mm
SFP+ module slots quantity	4	Height	44 mm
Console port	RJ-45	Weight	3.01 kg
		Packaging data	
		Package width	351 mm
		Package depth	565 mm
		Package height	91 mm

Network		Packaging data	
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Package weight	4.28 kg
10G support *	✓	Technical details	
Flow control support	✓	Shipping (inner) case height	38.4 cm
Link aggregation	✓	Shipping (inner) case width	47.8 cm
Broadcast storm control	✓	Shipping (inner) case length	58.5 cm
Auto MDI/MDI-X	✓	Shipping (inner) case net weight	18.3 kg
Spanning tree protocol	✓	Products per shipping (inner) case	5 pc(s)
Head-of-line (HOL) blocking	✓	Pallet gross weight (air)	382.7 kg
VLAN support	✓	Master (outer) cases per pallet (air)	16 pc(s)
Virtual LAN features	Voice VLAN	Products per pallet (air)	80 pc(s)
Number of VLANs	4094	Pallet gross length	110 cm
Optical fiber		Pallet gross width	120 cm
Fiber ethernet cabling technology	100BASE-FX, 1000BASE-LHX, 1000BASE-X, 1000BASE-LX, 1000BASE-SX, 1000BASE-ZX	Pallet height (air)	167.1 cm
Data transmission		Pallet gross weight (sea)	382.7 kg
Switching capacity *	176 Gbit/s	Master (outer) cases per pallet (sea)	16 pc(s)
Forwarding rate	130.95 Mpps	Products per pallet (sea)	80 pc(s)
MAC address table *	32000 entries	Pallet height (sea)	167.1 cm
Static route	✓	Shipping (inner) case gross weight	22.8 kg
Number of static routes	124	Certificates	
Jumbo frames support	✓	Certification	CB, UL, BSMI, CCC
Jumbo frames	12000	Logistics data	
Packet buffer memory	16 MB	Harmonized System (HS) code	85176990
Security			
DHCP features	DHCP client, DHCP server, DHCP snooping		
Access Control List (ACL)	✓		
Access Control List (ACL) rules	768		
IGMP snooping	✓		
Security algorithms	EAP, LEAP, MD5, PEAP, SSH, SSL/TLS, TTLS		
Loop protection	✓		
IP-MAC-Port binding	✓		
Queue scheduling algorithms	Weighted Round Robin (WRR)		
Multicast features			
Multicast support	✓		
Design			
Rack mounting *	✓		
Product colour	Black		
LED indicators	Activity, Link, Power, Speed		



0790069443015



790069443015

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.