

StarTech.com MCM1110MMLC verkon mediamuunnin 1000 Mbit/s 850 nm Monitila musta

Tuotemerkki : StarTech.com

Tuotekoodi: MCM1110MMLC

Tuotteen nimi : MCM1110MMLC

StarTech.com MCM1110MMLC. Tiedonsiirron enimmäisnopeus: 1000 Mbit/s, Muuntimen syöttöliittymä: 1000Base-T, 100Base-TX, 10Base-T, Muuntimen lähtöliittymä: 1000Base-LX, 1000Base-SX. Suurin siirtoetäisyys: 550 m, Aallonpituus: 850 nm, Valokuidun rakenne: Monitila. LED-merkkivalot: Toiminta/Seikkailu, Linkki, Teho, Tuotteen väri: musta, Koteloinen materiaali: Terästä. Valokuituliitin: LC, Yhteysteknologia: Langallinen. Tulojännite: 100 - 240 V, Syöttöjännite: 1 A, Ulostulojännite: 5 V



Network		Power	
Maximum data transfer rate *	1000 Mbit/s	Input voltage	100 - 240 V
Converter input interface	1000Base-T, 100Base-TX, 10Base-T	Input current	1 A
Converter output interface	1000Base-LX, 1000Base-SX	Output voltage	5 V
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3z	Output current	2 A
Ethernet interface type	Gigabit Ethernet	Power over Ethernet (PoE)	✗
Ethernet LAN data rates	10,100,1000 Mbit/s	External power adapter	✓
Data transfer rate	1000 Mbit/s	Power plug type	Type N
Jumbo frames support	✓	Weight & dimensions	
Auto MDI/MDI-X	✓	Width	70 mm
Duplex system	Full	Depth	94 mm
		Height	26 mm
		Weight	201 g
Performance		Operational conditions	
Maximum transfer distance *	550 m	Operating temperature (T-T)	0 - 50 °C
Wavelength *	850 nm	Storage temperature (T-T)	-10 - 70 °C
Wavelength-division multiplexing (WDM)	✗	Operating relative humidity (H-H)	5 - 95%
Fiber mode structure	Multi-mode	Packaging content	
Mean time between failures (MTBF)	50000 h	Manual	✓
Features		Packaging data	
Internal *	✗	Package width	140 mm
LED indicators	Activity, Link, Power	Package depth	284 mm
Product colour	Black	Package height	68 mm
Housing material	Steel	Package weight	556 g
Ports & interfaces		Certificates	
Connectivity technology	Wired	Compliance certificates	RoHS
Ethernet LAN (RJ-45) ports	1	Certification	CE, FCC, REACH, TAA
Fiber ports quantity	1		
Fiber optic connector *	LC		

Ports & interfaces

DC-in jack

**Logistics data**

Harmonized System (HS) code

85176990



0065030861465



065030861465



4053162878013

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.