StarTech.com

StarTech.com PEXUSB3S44V liitäntäkortti/-sovitin Sisäinen USB 3.2 Gen 1 (3.1 Gen 1)

Tuotemerkki : StarTech.com **Tuotekoodi:** PEXUSB3S44V

Tuotteen nimi : PEXUSB3S44V

StarTech.com PEXUSB3S44V. Isäntäkoneen käyttöliittymä: PCIe, Lähtöliitäntä: USB 3.2 Gen 1 (3.1 Gen 1), Laajennuskortin muotokerroin: Full-height / Low-profile. Tuotteen väri: musta, Kaapelin enimmäispituus: 3 m. Piirisarja: Renesas/NEC - µPD720202, Tiedonsiirtonopeus (maks.): 20 Gbit/s. Windows-käyttöjärjestelmätuki: Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10..., Tuetut palvelinkäyttöjärjestelmät: Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows.... Tuotteen leveys: 15 mm, Tuotteen syvyys: 167 mm, Tuotteen korkeus: 120 mm

Ports & interfaces

Host interface *	PCIe
Output interface *	USB 3.2 Gen 1 (3.1 Gen 1)
Expansion card form factor	Full-height / Low-profile
Expansion card standard	PCIe 2.0
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4
Peripheral (Molex) power connectors (4-pin)	1

Design

Internal *	✔
Product colour	Black
Maximum cable length	3 m

Features

Chipset	Renesas/NEC - µPD720202
Data transfer rate (max)	20 Gbit/s
UASP support	✔

Operational conditions

Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	5 - 85%

System requirements

Linux operating systems supported	✔
Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019

Technical details

Compliance certificates	RoHS

Weight & dimensions

Width	15 mm
Depth	167 mm
Height	120 mm
Weight	92 g

Packaging data

Drivers included	✔
Manual	✔
User guide	✔
Package width	145 mm
Package depth	208 mm
Package height	41 mm
Package weight	202 g

Logistics data

Harmonized System (HS) code	84733020
Products per master (outer) case	40 pc(s)
Master (outer) case width	418 mm
Master (outer) case length	441 mm
Master (outer) case height	313 mm

System requirements

Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows Vista x64

0065030854627

065030854627

5054484566939