

APC BR900MI UPS-virtalähde Linjainteraktiivinen 0,9 kVA 540 W 6 AC-pistorasia(a)

Tuotemerkki : APC Tuotekoodi: BR900MI

Tuotteen nimi: BR900MI


APC BR900MI. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 0,9 kVA, Lähtöteho: 540 W. Pistorasian tyypit: C13 liitin, Virtapistoke: C14 liitin, Ulostulojen määrä: 6 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kestoikä (maks.): 5 vuosi/vuosia, Akun latausaika: 12 h. Kotelo: Tower, Tuotteen väri: musta, Johdon pituus: 1,83 m. Tuotteen leveys: 91 mm, Tuotteen syvyys: 310 mm, Tuotteen korkeus: 190 mm





Features		Design	
UPS topology *	Line-Interactive	Form factor *	Tower
Output power capacity *	0.9 kVA	Cable length	1.83 m
Output power *	540 W	Cooling type	Passive
Waveform *	Sine	Product colour *	Black
Input operation voltage (min) *	176 V	Display type	LCD
Input operation voltage (max) *	294 V	LED indicators	✓
Input frequency *	50/60 Hz	Certification	A-tick, C-tick, CE, EAC, GS Mark, RCM, TISI
Output frequency	50/60 Hz		
Automatic Voltage Regulation (AVR)	✓	Operational conditions	
Maximum current	10 A	Operating temperature (T-T)	0 - 40 °C
Response time	12 ms	Storage temperature (T-T)	-15 - 45 °C
ECO mode	✓	Operating relative humidity (H-H)	0 - 95%
Noise level	45 dB	Storage relative humidity (H-H)	0 - 95%
Surge protection	✓	Operating altitude	0 - 3000 m
Surge protection features	Network	Non-operating altitude	0 - 15000 m
Audible alarm(s)	✓	Technical details	
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm	Sustainability certificates	Green Premium
Ports & interfaces		Weight & dimensions	
AC outlet types	C13 coupler	Width	91 mm
Power plug	C14 coupler	Depth	310 mm
AC outlets quantity	6 AC outlet(s)	Height	190 mm
USB port	✓	Weight	7.1 kg
		Package width	440 mm

Ports & interfaces		Weight & dimensions		
Ethernet LAN (RJ-45) ports Cabling technology	2 10/100/1000Base-T(X)	Package depth Package height Package weight	143 mm 255 mm 8 kg	
Battery Battery technology	Sealed Lead Acid (VRLA)	Packaging data	Packaging data	
Battery life (max)	5 year(s)	Cables included	USB cable	
Battery recharge time	12 h	Manual	✓	
Hot-swap battery	✓	Logistics data		
Automatic battery test	✓	Harmonized System (HS) code	85078000	
Cold start	✓	Other features		
		Nominal output voltage Nominal input voltage	230 V 230 V	





731304346944

0731304346944

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.