



APC BR1300MI UPS-virtalähde Linjainteraktiivinen 1,3 kVA 780 W 8 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: BR1300MI

Tuotteen nimi : BR1300MI

APC BR1300MI. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 1,3 kVA, Lähtöteho: 780 W. Pistorasian tyypit: C13 liitin, Virtapistoke: C14 liitin, Ulostulojen määrä: 8 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kestoikä (maks.): 5 vuosi/vuosia, Akun latausaika: 16 h. Kotelo: Tower, Tuotteen väri: musta, Johdon pituus: 1,83 m. Tuotteen leveys: 250 mm, Tuotteen syvyys: 382 mm, Tuotteen korkeus: 100 mm



Features		Design	
UPS topology *	Line-Interactive	Form factor *	Tower
Output power capacity *	1.3 kVA	Cable length	1.83 m
Output power *	780 W	Cooling type	Passive
Waveform *	Sine	Product colour *	Black
Input operation voltage (min) *	176 V	Display type	LCD
Input operation voltage (max) *	294 V	LED indicators	✓
Input frequency *	50/60 Hz	Certification	A-tick, C-tick, CE, EAC, GS Mark, RCM, TISI
Output frequency	50/60 Hz		
Automatic Voltage Regulation (AVR)	✓		
Maximum current	10 A		
Surge energy rating	509 J		
ECO mode	✓		
Noise level	45 dB		
Surge protection	✓		
Surge protection features	Network		
Audible alarm(s)	✓		
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm		
Ports & interfaces		Operational conditions	
AC outlet types	C13 coupler	Operating temperature (T-T)	0 - 40 °C
Power plug	C14 coupler	Storage temperature (T-T)	-15 - 45 °C
AC outlets quantity	8 AC outlet(s)	Operating relative humidity (H-H)	0 - 95%
USB port	✓	Storage relative humidity (H-H)	0 - 95%
		Operating altitude	0 - 3000 m
		Non-operating altitude	0 - 15000 m
		Technical details	
		Sustainability certificates	Green Premium
		Weight & dimensions	
		Width	250 mm
		Depth	382 mm
		Height	100 mm
		Weight	10.2 kg
		Package width	485 mm

Ports & interfaces		Weight & dimensions	
USB 2.0 ports quantity	1	Package depth	225 mm
Ethernet LAN (RJ-45) ports	2	Package height	330 mm
Cabling technology	10/100/1000Base-T(X)	Package weight	11.8 kg
Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Cables included	USB cable
Battery life (max)	5 year(s)	Manual	✓
Battery recharge time	16 h		
Hot-swap battery	✓	Logistics data	
Automatic battery test	✓	Harmonized System (HS) code	85078000
Cold start	✓	Other features	
		Nominal output voltage	230 V
		Nominal input voltage	230 V



0731304346906



731304346906

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.