



APC Back-UPS Pro, 1600VA/960W, Tower, 230V, 8x IEC C13 outlets, Sine Wave, AVR, USB Type A + C ports, LCD, User Replaceable Battery

Brand : APC

Product code: BR1600SI

Product name : Back-UPS Pro, 1600VA/960W, Tower, 230V, 8x IEC C13 outlets, Sine Wave, AVR, USB Type A + C ports, LCD, User Replaceable Battery

Back-UPS Pro, 1600VA/960W, Tower, 230V, 8x IEC C13 outlets, Sine Wave, AVR, USB Type A + C ports, LCD, User Replaceable Battery

APC Back-UPS Pro, 1600VA/960W, Tower, 230V, 8x IEC C13 outlets, Sine Wave, AVR, USB Type A + C ports, LCD, User Replaceable Battery. UPS topology: Line-Interactive, Output power capacity: 1.6 kVA, Output power: 960 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 8 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 260 Ah, Battery life (max): 5 year(s). Form factor: Mini Tower, Product colour: Black, Display type: LCD. Width: 100 mm, Depth: 368 mm, Height: 260 mm



Features		Battery	
UPS topology *	Line-Interactive	Battery recharge time	16 h
Output power capacity *	1.6 kVA	Hot-swap battery	✓
Output power *	960 W	Automatic battery test	✓
Waveform *	Sine	Cold start	✓
Input operation voltage (min) *	176 V		
Input operation voltage (max) *	294 V		
Input frequency *	50/60 Hz		
Output operation voltage (max)	230 V		
Output frequency	50/60 Hz		
Automatic Voltage Regulation (AVR)	✓		
Maximum current	10 A		
Surge energy rating	509 J		
Noise level	45 dB		
Power protection features	Overload		
Audible alarm(s)	✓		
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm		
Ports & interfaces		Design	
AC outlet types	C13 coupler	Form factor *	Mini Tower
Power plug	C14 coupler	Product colour *	Black
AC outlets quantity	8 AC outlet(s)	Display type	LCD
USB port	✓	Certification	A-tick, C-tick, CE, EAC, GS Mark, RCM, TISI, REACH
USB 2.0 ports quantity	2		
Ethernet LAN (RJ-45) ports	1		
Battery		Operational conditions	
Battery technology	Sealed Lead Acid (VRLA)	Operating temperature (T-T)	0 - 40 °C
		Storage temperature (T-T)	-15 - 45 °C
		Operating relative humidity (H-H)	0 - 95%
		Storage relative humidity (H-H)	0 - 95%
		Operating altitude	0 - 3000 m
		Non-operating altitude	0 - 15000 m
		Technical details	
		Sustainability certificates	Green Premium
		Compliance certificates	RoHS
		Weight & dimensions	
		Width	100 mm
		Depth	368 mm
		Height	260 mm
		Weight	12.1 kg

Battery		Weight & dimensions	
Battery capacity	260 Ah	Package width	223 mm
Number of batteries supported	1	Package depth	482 mm
Battery life (max)	5 year(s)	Package height	359 mm
		Package weight	13.8 kg
Logistics data			
		Harmonized System (HS) code	85078000



0731304346920



731304346920

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 05-NOV-2024. Prints or copies of Information are only valid on the printed Publication date