



APC BR1600SI UPS-virtalähde Linjainteraktiivinen 1,6 kVA 960 W 8 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: BR1600SI

Tuotteen nimi : BR1600SI

APC BR1600SI. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 1,6 kVA, Lähtöteho: 960 W. Pistorasian tyypit: C13 liitin, Virtapistoke: C14 liitin, Ulostulojen määrä: 8 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 260 ah, Akun kestoikä (maks.): 5 vuosi/vuosia. Kotelo: Mini Tower, Tuotteen väri: musta, Näytön tyyppi: LCD. Vaatimustenmukaisuustodistukset: RoHS, Sertifointi: A-tick, C-tick, CE, EAC, GS Mark, RCM, TISI, REACH



Features		Battery	
UPS topology *	Line-Interactive	Hot-swap battery	✓
Output power capacity *	1.6 kVA	Automatic battery test	✓
Output power *	960 W	Cold start	✓
Waveform *	Sine		
Input operation voltage (min) *	176 V		
Input operation voltage (max) *	294 V		
Input frequency *	50/60 Hz		
Output operation voltage (max)	230 V		
Output frequency	50/60 Hz		
Automatic Voltage Regulation (AVR)	✓		
Maximum current	10 A		
Surge energy rating	509 J		
Noise level	45 dB		
Power protection features	Overload		
Audible alarm(s)	✓		
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm		
Ports & interfaces		Design	
AC outlet types	C13 coupler	Form factor *	Mini Tower
Power plug	C14 coupler	Product colour *	Black
AC outlets quantity	8 AC outlet(s)	Display type	LCD
USB port	✓		
USB 2.0 ports quantity	2		
Ethernet LAN (RJ-45) ports	1		
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Storage temperature (T-T)	-15 - 45 °C
		Operating relative humidity (H-H)	0 - 95%
		Storage relative humidity (H-H)	0 - 95%
		Operating altitude	0 - 3000 m
		Non-operating altitude	0 - 15000 m
		Certificates	
		Compliance certificates	RoHS
		Certification	A-tick, C-tick, CE, EAC, GS Mark, RCM, TISI, REACH
		Sustainability	
		Sustainability certificates	Green Premium
		Weight & dimensions	
		Width	100 mm
		Depth	368 mm
		Height	260 mm

Battery		Weight & dimensions	
Battery technology	Sealed Lead Acid (VRLA)	Weight	12.1 kg
Battery capacity	260 Ah	Packaging data	
Number of batteries supported	1	Package width	223 mm
Battery life (max)	5 year(s)	Package depth	482 mm
Battery recharge time	16 h	Package height	359 mm
		Package weight	13.8 kg
		Logistics data	
		Harmonized System (HS) code	85078000



0731304346920



731304346920

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.