

GCS922DPKIT

2-Port USB DVI Cable KVM with DisplayPort Adapters Bundle



DVI and DisplayPort Mix & Match Solution

IOGEAR's DVI and DisplayPort KVM Solution simplifies the method of sharing two computers using one DVI monitor, keyboard and mouse. This bundle is perfect for a home office or small / medium size business, as it offers the flexibility of choosing between DVI and/or DisplayPort connections. Take advantage of your existing computers, and use the included DisplayPort adapters to view your content on a DVI projector, monitor, or display. Streamline and develop efficient workstations by eliminating multiple desktop setups.

Straight Forward Connectivity

Switch and control any of the two connected computers easily via remote push button. This 2-Port DVI - DisplayPort switch does not require external power and supports USB hot-plugging, making it easy to add or remove USB computers connected to the KVM. Expand your USB peripheral sharing by using the USB mouse port. This DVI - DisplayPort KVM bundle supports video resolution up to 1920 x 1200 @ 60Hz, giving users excellent, crisp images on the screen every time.


Secure Switching

This DVI KVM switch also offers a cost effective solution to increase security by allowing users to switch between the Internet connected PC and an Intranet connected PC. With built-in cables and included adapters, IOGEAR's 2-Port USB DVI and DisplayPort KVM bundle is a true out-of-the-box Plug-N-Play solution to your connectivity needs!


- Connect and control two DVI-D or DisplayPort USB 2.0 interface computers with a single keyboard and mouse
- Video resolution – up to 1920 x 1200 @60Hz
- USB mouse port can be used for USB peripheral sharing, such as external storage drive
- Computer Selection via push-button Remote Port Selector
- Supports USB hot-plugging
- Power supply not required
- DisplayPort to DVI Adapters:
 - Compliant with DisplayPort Specification 1.1a for both 1.62 Gbps and 2.7 Gbps
 - Support full DisplayPort link tracking
 - Compliant with DVI 1.0 up to 1.65Gbps
 - Supports interrupt request output for expansion function
 - Supports Deep Sleep Mode (suspend mode)



Solution 1



Solution 2



Requirements

Package Contents

- | | |
|--|---|
| <ul style="list-style-type: none"> • Console: • 1 DVI display • 1 set of USB keyboard and mouse • • Computers: • 1 DVI-D Port or DisplayPort • 1 USB Ports • • Operating Systems: • Windows Vista®, Windows® 7, Windows® 8, Windows® 8.1, Windows® 10 • Mac OS 9 to 10.x • Oracle® Solaris • Linux®, Unix and other USB supported systems* | <ul style="list-style-type: none"> • 1 x GCS922U • 2 x DisplayPort to DVI Adapters • 1 x Quick Start Guide • 1 x Warranty |
|--|---|

*Additional drivers and support may be needed

Specifications

Function	GCS922DPKIT	Dimensions	GCS922DPKIT
Computer Connections		POP Information	
Direct	2	10" Peg Hook	5
Console Connectors		6" Peg Hook	3
Monitor	1 x DVI-D	Unit Dimensions	
Keyboard	1 x USB Type A Female	Height	1.06" (2.69cm)
Mouse	1 x USB Type A Female	Depth	4.06" (10.3cm)
CPU Connectors		Length	3.44" (8.74cm)
Monitor	2 x DVI-D Male; 2 x DisplayPort Male (adapters)	Unit Package Dimensions	
Keyboard & Mouse	2 x USB Type A Male	Width	6.13" (15.6cm)
LEDs		Height	8.81" (22.4cm)
On Line	2 x Green	Depth	2.25" (5.72cm)
Video Resolution		Master Carton	
	1900x1200 @60Hz	Width	6.75" (17.1cm)
Environment		Height	15" (38.1cm)
Storage Temperature	-20-60°C	Depth	8" (20.3cm)
Operation Temperature	0-50°C	Master Carton Qty.	6
Humidity	0-80%; Non-condensing	Weight	
Port Selection		Master Carton Wt.	7.2lb (3.27kg)
	Remote Switch	Unit Pack Wt.	1.1lb (0.5kg)
Cable Length		Unit Wt. w/accessories	0.85lb (0.39kg)
	2 x 4ft. ea KVM cables; 1 x 6ft. Remote Switch	Unit Wt.	0.75lb (0.34kg)
Cable Type			
	Bonded USB KVM		
Housing			
Case	Plastic		