

ZYXEL

## Zyxel WAX650S 3550 Mbit/s Valkoinen Power over Ethernet -tuki

**Tuotemerkki :** Zyxel

**Tuotekoodi :** WAX650S-EU0101F

**Tuotteen nimi :** WAX650S

Zyxel WAX650S. 2,4 GHz, 5 GHz, Tiedonsiirron enimmäisnopeus: 3550 Mbit/s. Tietoturva-algoritmit: SNMP, WEP, WPA-Enterprise, WPA-PSK, WPA2, WPA3. Ethernet LAN -datanopeudet: 1000,2500,5000 Mbit/s. Power over Ethernet -tuki. Tuotteen väri: Valkoinen



Features		Design	
2.4 GHz *	✓	Product colour *	White
5 GHz *	✓	<b>Antenna</b>	
Maximum data transfer rate *	3550 Mbit/s	Antenna type *	Internal
Maximum data transfer rate (2.4 GHz)	1150 Mbit/s	Antenna gain level (max)	5.8 dBi
Maximum data transfer rate (5 GHz)	2400 Mbit/s	<b>Certificates</b>	
Ethernet LAN data rates	1000,2500,5000 Mbit/s	Certification	FCC 15C, FCC 15E, ETSI EN 300 328, EN 301 893, LP0002 FCC 15B, EN 301 489-1, EN 301 489-17, EN55022, EN55024, EN61000-3-2/-3, EN60601-1-2, BSMI CNS13438 EN 60950-1, IEC 60950-1, BSMI CNS14336-1
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3bt	<b>Weight &amp; dimensions</b>	
MIMO	✓	Width	230 mm
MIMO type	Multi User MIMO	Depth	235 mm
Wi-Fi Multimedia (WMM)/(WME)	✓	Height	53.5 mm
Fast roaming	✓	Weight	1.16 kg
VLAN support	✓	<b>Packaging data</b>	
Wireless isolation	✓	Package width	282 mm
Band steering	✓	Package depth	266 mm
Transmitting power	26 dBmW	Package height	79 mm
Receiver sensitivity	-105 dBm	Package weight	1.49 kg
<b>Security</b>		<b>Packaging content</b>	
Security algorithms *	SNMP, WEP, WPA-Enterprise, WPA-PSK, WPA2, WPA3	Quantity per pack	1 pc(s)
MAC address filtering	✓	Mounting kit	✓
Auto Wireless Distribution System (WDS)	✓	<b>Operational conditions</b>	
<b>Management features</b>		Operating relative humidity (H-H)	10 - 95%
Web-based management	✓		

Management features		Operational conditions	
Firmware upgradeable	✓	Operating temperature (T-T)	0 - 50 °C
Ports & interfaces		Storage temperature (T-T)	-30 - 70 °C
Ethernet LAN (RJ-45) ports *	2	Storage relative humidity (H-H)	10 - 90%
DC-in jack	✓	Logistics data	
Power		Harmonized System (HS) code	85176990
Power over Ethernet (PoE) *	✓		
AC input voltage	12 V		



4718937609178

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-DEC-2024. Prints or copies of Information are only valid on the printed Publication date