

## StarTech.com DK30C2DPPDUE kannettavien tietokoneiden telakka ja porttitoistin Langallinen USB 3.2 Gen 1 (3.1 Gen 1) Type-C musta, Harmaa

**Tuotemerkki** : StarTech.com

**Tuotekoodi**: DK30C2DPPDUE

**Tuotteen nimi** : DK30C2DPPDUE



StarTech.com DK30C2DPPDUE. Yhteysteknologia: Langallinen, Isäntäkoneen käyttöliittymä: USB 3.2 Gen 1 (3.1 Gen 1) Type-C, USB Power Delivery asti: 60 W. Verkkostandardit: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u. Tuotteen väri: musta, Harmaa, Tiedonsiirtonopeus: 5 Gbit/s, Digitaalinen enimmäistarkkuus: 5120 x 2880 pikseliä. AC-syöttöjännite: 100 - 240 V, Syöttöjännite: 2.5 A, Ulostulojännite: 20 V. Windows-käyttöjärjestelmätuki: Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10..., Mac-käyttöjärjestelmätuki: Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina,..., Muu käyttöjärjestelmätuki: ChromeOS

| Ports & interfaces                                |                                       | Software                            |  |
|---|---------------------------------------|-------------------------------------|--|
| Connectivity technology *                         | Wired                                 |                                     | Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows 95 |
| Host interface *                                  | USB 3.2 Gen 1 (3.1 Gen 1) Type-C      |                                     |  |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * | 3                                     |                                     |  |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity   | 1                                     |                                     |  |
| USB Power Delivery (USB PD)                       | ✓                                     |                                     |  |
| USB Power Delivery up to                          | 60 W                                  |                                     |  |
| HDMI ports quantity *                             | 2                                     |                                     |  |
| DisplayPorts quantity                             | 2                                     |                                     |  |
| Combo headphone/mic port                          | ✓                                     | Windows operating systems supported |  |
| Headphone outputs *                               | 1                                     |                                     |  |
| Headphone connectivity                            | 3.5 mm                                |                                     |  |
| DC-in jack  | ✓                                     |                                     |  |
| Network   |                                       |                                     |  |
| Ethernet LAN *                                    | ✓                                     |                                     |  |
| Ethernet LAN (RJ-45) ports                        | 1                                     |                                     |  |
| Networking standards                              | IEEE 802.3, IEEE 802.3ab, IEEE 802.3u |                                     |  |
| Full duplex                                       | ✓                                     |                                     |  |
| 10G support                                       | ✗                                     | Mac compatibility                   | ✓  |
| Performance                                       |                                       | Mac operating systems supported     | Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 13.0 Ventura  |
| Card reader integrated *                          | ✗                                     | Other operating systems supported   | ChromeOS   |
| Data transfer rate                                | 5 Gbit/s                              |                                     |  |
| Maximum digital resolution                        | 5120 x 2880 pixels                    |                                     |  |
| Cable lock slot                                   | ✓                                     |                                     |  |
| Cable lock slot type                              | Kensington                            |                                     |  |
| Product colour *                                  | Black, Grey                           |                                     |  |
|   |                                       | Operational conditions              |  |
|   |                                       | Operating temperature (T-T)         | 0 - 50 °C  |
|   |                                       | Storage temperature (T-T)           | -20 - 70 °C  |

|                             |                |                                   |   |
|-----------------------------|----------------|-----------------------------------|---|
| <b>Performance</b>          |                | <b>Operational conditions</b>     |   |
| UASP support                | ✓              | Operating relative humidity (H-H) | 0 - 95%   |
| Housing material            | Plastic        | <b>Weight &amp; dimensions</b>    |   |
| Certification               | CE, FCC, REACH | Width                             | 80 mm   |
| <b>Power</b>                |                | Depth                             | 220 mm  |
| AC input voltage            | 100 - 240 V    | Height                            | 30 mm   |
| Input current               | 2.5 A          | Weight                            | 280 g   |
| Output voltage              | 20 V           | <b>Packaging data</b>             |   |
| Output current              | 6.75 A         | Package width                     | 160 mm  |
| Power consumption (typical) | 135 W          | Package depth                     | 270 mm  |
| Power plug type             | Type N         | Package height                    | 105 mm  |
| Compatible power plug types | EU, UK         | Package weight                    | 1.3 kg  |
|                             |                | <b>Packaging content</b>          |   |
|                             |                | Cables included                   | USB Type-A to USB Type-C  |
|                             |                | AC adapter included               | ✓   |
|                             |                | Quick start guide                 | ✓   |
|                             |                | <b>Technical details</b>          |   |
|                             |                | Compliance certificates           | RoHS  |
|                             |                | <b>Logistics data</b>             |   |
|                             |                | Products per master (outer) case  | 6 pc(s)   |
|                             |                | Master (outer) case width         | 295 mm  |
|                             |                | Master (outer) case length        | 500 mm  |
|                             |                | Master (outer) case height        | 250 mm  |
|                             |                | Harmonized System (HS) code       | 84733020  |
|                             |                | <b>Other features</b>             |   |
|                             |                | Chipset                           | DisplayLink - DL6950, Genesys Logic - GL3523, Fresco Logic - FL7102, Fresco Logic - FL7201, VIA Labs - VL160, RealTek - RTL8153, Texas Instruments - TS3A225E |



0065030879965



065030879965

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.