EPSON

Epson TM-m10 203 x 203 DPI Wired Direct thermal POS printer

Brand : Epson

Product name : TM-m10

Product code: C31CE74101

2" receipt printer, thermal, 203 dpi, USB, white, 900g

Epson TM-m10 203 x 203 DPI Wired Direct thermal POS printer:

POS printing reimagined with a compact, sleek, 2" receipt printer

The industry's smallest POS 2" receipt printer in its class, the TM-m10 saves valuable counter space, while offering the freedom to print receipts from virtually any mobile device and/or desktop PC. Ideal for most environments, its modular casing can be easily switched from a top-load to front-load configuration. This versatile printer ensures simple integration with existing mobile POS environments, intuitive functionality and advanced connectivity. The TM-m10 is the first of its kind designed exclusively for small businesses. Featuring ePOS™ print technology, it works with iOS®, Android™ and Windows® mobile devices and desktop PCs, and offers fast, easy setup.

Printing

Colour	✘
Maximum resolution	203 x 203 DPI
Print speed	150 mm/sec
Print speed (receipt)	150 mm/sec
Printing characters	Text, Graphic, Barcode
Character sets	ANK
Print technology *	Direct thermal
Type *	POS printer

Paper handling

Maximum roll diameter	6 cm
Supported paper width	58 mm
Maximum printing width	5.25 cm
Media thickness	48 - 80 mm

Ports & interfaces

USB port *	✔
USB 2.0 ports quantity	1
Bluetooth	✘
Connectivity technology *	Wired
Near Field Communication (NFC)	✔
Standard interfaces	USB 2.0

Network

Ethernet LAN *	✘
Wi-Fi *	✘

Features

Built-in barcodes *	CODABAR (NW-7), Code 39, Code 93, EAN13, EAN8, GS1 DataBar, GS1-128, ITF, UPC-A, UPC-E
Sound pressure level (printing)	55 dB
Mean time between failures (MTBF)	360000 h
Cutter	✔
Half-cutter	✔
Autocutter durability	1 million cuts
Print head life	100 km
Country of origin	China
Mounting position	Horizontal/Vertical
Built-in sensors details	Paper End Sensor, Papier-Sensor

Operational conditions

Storage relative humidity (H-H)	10 - 90%

System requirements

Mobile operating systems supported	Android, Windows Mobile, iOS

Weight & dimensions

Width	102 mm
Depth	102 mm
Height	102 mm
Weight	900 g

Packaging data

Cables included	USB
Quantity per pack	1 pc(s)
Package width	195 mm
Package depth	235 mm
Package height	175 mm
Package weight	1.67 kg

Packaging content

Drivers included	✔
Quick start guide	✔
AC adapter included	✔

Print technology

Column capacity	35/42

Logistics data

Pallet weight (UK)	0 g
Harmonized System (HS) code	84433210
Products per master (outer) case	8 pc(s)
Master (outer) case width	400 mm
Master (outer) case length	490 mm
Master (outer) case height	360 mm
Master (outer) case gross weight	0 g
Products per pallet	160 pc(s)
Products per pallet layer	32 pc(s)
Pallet gross width	80 cm
Pallet gross length	120 cm
Pallet gross height	102.5 cm
Pallet gross weight	0 g
Products per pallet (UK)	240 pc(s)

Features

Safety	EMI FCC Class A, CAN ICES-3(A)/NMB-3(A), UL60950-1/CSA C22.2 No.60950-1

Design

Product colour *	White

Power

Power consumption (printing)	15.9 W
Power plug type	Type C
Input current	1.5 A
Power supply type	DC
Power consumption	1500 mA
Power consumption (standby)	100 mA

Operational conditions

Operating temperature (T-T)	5 - 45 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	10 - 90%

Logistics data

Products per pallet layer (UK)	48 pc(s)
Pallet width (UK)	100 cm
Pallet length (UK)	120 cm
Pallet height (UK)	102.5 cm

Technical details

Font styles	ANK
Lifetime	15000000 lines

Other features

Buffer size	64 KB
LED indicators	✔
Mean cycles between failures (MCBF)	60000000
Print head life	100.000.000 Impulse

8715946641003