

## Epson TM-m10 203 x 203 DPI Wired Direct thermal POS printer

**Brand :** Epson

**Product code:** C31CE74102

**Product name :** TM-m10

2" receipt printer, thermal, 203 dpi, USB, black, 900g

[Epson TM-m10 203 x 203 DPI Wired Direct thermal POS printer:](#)

### POS printing reimagined with a compact, sleek, 2" receipt printer

The industry's smallest POS 2" receipt printer in its class, the TM-m10 saves valuable counter space, while offering the freedom to print receipts from virtually any mobile device and/or desktop PC. Ideal for most environments, its modular casing can be easily switched from a top-load to front-load configuration. This versatile printer ensures simple integration with existing mobile POS environments, intuitive functionality and advanced connectivity. The TM-m10 is the first of its kind designed exclusively for small businesses. Featuring ePOS™ print technology, it works with iOS®, Android™ and Windows® mobile devices and desktop PCs, and offers fast, easy setup.



<b>Printing</b>		<b>Operational conditions</b>	
Colour	✗	Storage relative humidity (H-H)	10 - 90%
Maximum resolution	203 x 203 DPI	<b>System requirements</b>	
Print speed	150 mm/sec	Mobile operating systems supported	Android, Windows Mobile, iOS
Print speed (receipt)	150 mm/sec	<b>Weight &amp; dimensions</b>	
Printing characters	Text, Graphic, Barcode	Width	102 mm
Character sets	ANK	Depth	102 mm
Print technology *	Direct thermal	Height	102 mm
Type *	POS printer	Weight	900 g
<b>Paper handling</b>		<b>Packaging data</b>	
Maximum roll diameter	6 cm	Cables included	USB
Supported paper width	58 mm	Quantity per pack	1 pc(s)
Maximum printing width	5.25 cm	Package width	195 mm
Media thickness	48 - 80 mm	Package depth	235 mm
<b>Ports &amp; interfaces</b>		Package height	175 mm
USB port *	✓	Package weight	1.66 kg
USB 2.0 ports quantity	1	<b>Packaging content</b>	
Bluetooth	✗	Drivers included	✓
Connectivity technology *	Wired	Quick start guide	✓
Near Field Communication (NFC)	✓	AC adapter included	✓
Standard interfaces	USB 2.0	<b>Print technology</b>	
<b>Network</b>		Column capacity	35/42
Ethernet LAN *	✗	<b>Logistics data</b>	
Wi-Fi *	✗	Pallet weight (UK)	0 g
		Harmonized System (HS) code	84433210

Features		Logistics data	
Built-in barcodes *	CODABAR (NW-7), Code 39, Code 93, EAN13, EAN8, GS1 DataBar, GS1-128, ITF, UPC-A, UPC-E	Products per master (outer) case	8 pc(s)
Sound pressure level (printing)	55 dB	Master (outer) case width	400 mm
Mean time between failures (MTBF)	360000 h	Master (outer) case length	490 mm
Cutter	✓	Master (outer) case height	360 mm
Half-cutter	✓	Master (outer) case gross weight	0 g
Autocutter durability	1 million cuts	Products per pallet	160 pc(s)
Print head life	100 km	Products per pallet layer	32 pc(s)
Country of origin	China	Pallet gross width	80 cm
Mounting position	Horizontal/Vertical	Pallet gross length	120 cm
Built-in sensors details	Paper End Sensor, Papier-Sensor	Pallet gross height	102.5 mm
Safety	EMI FCC Class A, CAN ICES-3(A)/NMB-3(A), UL60950-1/CSA C22.2 No.60950-1	Pallet gross weight	0 g
		Products per pallet (UK)	240 pc(s)
		Products per pallet layer (UK)	48 pc(s)
		Pallet width (UK)	100 cm
		Pallet length (UK)	120 cm
		Pallet height (UK)	102.5 cm
Design		Technical details	
Product colour *	Black	Font styles	ANK
		Lifetime	15000000 lines
Power		Other features	
Power consumption (printing)	15.9 W	Buffer size	64 KB
Power plug type	Type C	LED indicators	✓
Input current	1.5 A	Mean cycles between failures (MCBF)	60000000
Power supply type	DC	Print head life	100.000.000 Impulse
Power consumption	1500 mA		
Power consumption (standby)	100 mA		
Operational conditions			
Operating temperature (T-T)	5 - 45 °C		
Storage temperature (T-T)	-20 - 60 °C		
Operating relative humidity (H-H)	10 - 90%		



8715946641010

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-DEC-2024. Prints or copies of Information are only valid on the printed Publication date