

Epson TM-m10 203 x 203 DPI Wired & Wireless Direct thermal POS printer



Brand : Epson

Product code: C31CE74111

Product name : TM-m10

2" receipt printer, thermal, 203 dpi, bluetooth, white, EU, 900g

[Epson TM-m10 203 x 203 DPI Wired & Wireless Direct thermal POS printer:](#)

POS printing reimagined with a compact, sleek, 2" receipt printer

The industry's smallest POS 2" receipt printer in its class, the TM-m10 saves valuable counter space, while offering the freedom to print receipts from virtually any mobile device and/or desktop PC. Ideal for most environments, its modular casing can be easily switched from a top-load to front-load configuration. This versatile printer ensures simple integration with existing mobile POS environments, intuitive functionality and advanced connectivity. The TM-m10 is the first of its kind designed exclusively for small businesses. Featuring ePOS™ print technology, it works with iOS®, Android™ and Windows® mobile devices and desktop PCs, and offers fast, easy setup.

| Printing | | Operational conditions | |
|-----------------------------------|--|------------------------------------|------------------------------|
| Colour | ✗ | Storage temperature (T-T) | -20 - 60 °C |
| Maximum resolution | 203 x 203 DPI | Operating relative humidity (H-H) | 10 - 90% |
| Print speed | 150 mm/sec | Storage relative humidity (H-H) | 10 - 90% |
| Print speed (receipt) | 150 mm/sec | System requirements | |
| Character sets | ANK | Mobile operating systems supported | Android, Windows Mobile, iOS |
| Print technology * | Direct thermal | Weight & dimensions | |
| Type * | POS printer | Width | 102 mm |
| Paper handling | | Depth | 102 mm |
| Maximum roll diameter | 6 cm | Height | 102 mm |
| Supported paper width | 57.5 mm | Weight | 900 g |
| Maximum printing width | 5.25 cm | Packaging data | |
| Ports & interfaces | | Cables included | USB |
| USB port * | ✓ | Quantity per pack | 1 pc(s) |
| USB 2.0 ports quantity | 1 | Package width | 197 mm |
| Bluetooth | ✓ | Package depth | 237 mm |
| Bluetooth version | 3.0+HS | Package height | 179 mm |
| Connectivity technology * | Wired & Wireless | Package weight | 1.58 kg |
| Near Field Communication (NFC) | ✓ | Packaging content | |
| Standard interfaces | Bluetooth, USB 2.0 | Drivers included | ✓ |
| Network | | Quick start guide | ✓ |
| Ethernet LAN * | ✗ | AC adapter included | ✓ |
| Ethernet LAN data rates | 10,100 Mbit/s | Print technology | |
| Wi-Fi * | ✗ | Column capacity | 35/42 |
| Features | | Logistics data | |
| Built-in barcodes * | CODABAR (NW-7), Code 39, Code 93, EAN13, EAN8, GS1 DataBar, GS1-128, ITF, UPC-A, UPC-E | Pallet weight (UK) | 0 g |
| Sound pressure level (printing) | 55 dB | Products per pallet | 160 pc(s) |
| Mean time between failures (MTBF) | 360000 h | Products per pallet layer | 32 pc(s) |
| Cutter | ✓ | Pallet gross width | 80 cm |
| Half-cutter | ✓ | Pallet gross length | 120 cm |
| Autocutter durability | 1 million cuts | Pallet gross height | 95 cm |
| Print head life | 100 km | Pallet gross weight | 0 g |
| Country of origin | China | Products per pallet (UK) | 240 pc(s) |
| Mounting position | Horizontal/Vertical | Products per pallet layer (UK) | 48 pc(s) |
| | | Pallet width (UK) | 100 cm |
| | | Pallet length (UK) | 120 cm |

| Features | | Logistics data | |
|-------------------------------|---|-------------------------------------|------------------------------|
| Built-in sensors details | Paper End Sensor, Papier-Sensor | Pallet height (UK) | 95 cm |
| Safety | EMI FCC Class A, CAN ICES-3(A)/NMB-3(A), UL60950-1/CSA C22.2 No.60950-1 | Technical details | |
| Design | | Font styles | ANK |
| Product colour * | White | Lifetime | 15000000 lines |
| Power | | Other features | |
| Power consumption (printing) | 15.9 W | Buffer size | 64 KB |
| Power plug type | Type C | LED indicators | ✓ |
| Input current | 1.5 A | Mean cycles between failures (MCBF) | 60000000 |
| Power supply type | DC | Print head life | 100 km - 100.000.000 Impulse |
| Power consumption | 1500 mA | | |
| Power consumption (standby) | 100 mA | | |
| Operational conditions | | | |
| Operating temperature (T-T) | 5 - 45 °C | | |



8715946605852

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-DEC-2024. Prints or copies of Information are only valid on the printed Publication date