Epson TM-T88VI (111P0) 180 x 180 DPI Wired & Wireless Direct thermal POS printer

Brand : Epson

Product code: C31CE94111P0

Product name : TM-T88VI (111P0)

- Fast print speeds: Print at speeds of up to 350mm/s
- Proven reliability: Epson's proven track record for reliability
- Co-existence: Allows PC, mobile and web connection at the same time
- Server direct print: Print directly from web server to any connected receipt printer
- Beacon support: Lets mobile devices print to the nearest available printer
180 x 180DPI, 350mm/sec, USB 2.0, RS-232, Ethernet
Epson TM-T88VI (111P0). Print technology: Direct thermal, Type: POS printer, Maximum resolution: 180 x 180 DPI. Maximum roll diameter: 8.3 cm, Supported paper width: 80 mm, Media thickness: 48 - 80 mm. Connectivity technology: Wired & Wireless, USB connector: USB Type-A / USB Type-B, Serial interface type: RS-232. Mean time between failures (MTBF): 360000 h, Autocutter durability: 3 million cuts, Print head life: 200 km. Product colour: Black

Printing

Maximum resolution	180 x 180 DPI
Print speed	300 mm/sec
Print speed (receipt)	350 mm/sec
Printing characters	Text, Graphic, Barcode
Character sets	ANK
Print technology *	Direct thermal
Type *	POS printer

Paper handling

Maximum roll diameter	8.3 cm
Supported paper width	80 mm
Media thickness	48 - 80 mm

Ports & interfaces

USB port *	✔
USB connector	USB Type-A / USB Type-B
Serial interface *	✔
Serial interface type	RS-232
Connectivity technology *	Wired & Wireless
Near Field Communication (NFC)	✔
Standard interfaces	Ethernet, NFC, RS-232, USB 2.0

Network

Ethernet LAN *	✔

Features

Mean time between failures (MTBF)	360000 h
Cutter	✔
Half-cutter	✔
Autocutter durability	3 million cuts

Operational conditions

Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 90%

System requirements

Pre-installed software	Print Data Notification

Weight & dimensions

Width	145 mm
Depth	195 mm
Height	148 mm
Weight	1.6 kg

Packaging data

Quantity per pack	1 pc(s)
Package width	193 mm
Package depth	240 mm
Package height	235 mm
Package weight	2.6 kg

Print technology

Column capacity	58/80

Logistics data

Pallet weight (UK)	0 g
Harmonized System (HS) code	84433210
Products per master (outer) case	4 pc(s)
Master (outer) case width	400 mm
Master (outer) case length	490 mm
Master (outer) case height	255 mm
Master (outer) case gross weight	0 g
Products per pallet	128 pc(s)
Pallet gross weight	0 g

Features

Print head life	200 km
Country of origin	China
Mounting position	Horizontal
Wall mountable	✔
Built-in sensors details	Paper Near End Sensor, Cover Open Sensor, Papier-Sensor
Safety	UL, CSA
Certification	CE, EN55024

Design

Product colour *	Black

Power

AC input voltage	24 V
Power plug type	Type C

Operational conditions

Operating temperature (T-T)	5 - 45 °C
Storage temperature (T-T)	-10 - 50 °C

Logistics data

Products per pallet (UK)	192 pc(s)

Technical details

Changeable interface	✔
Lifetime	20000000 lines
Master (outer) case GTIN (EAN/UPC)	8715946696409

Other features

Buffer size	4 KB
Electromagnetic compatibility	CE marking, EN55024
Mean cycles between failures (MCBF)	70000000
Print head life	200.000.000 Impulse

8715946640983