tp-link

TP-Link TL-PA7017P KIT PowerLine-verkkosovitin 1000 Mbit/s Ethernet LAN Valkoinen 2 kpl

Tuotemerkki : TP-Link   **Tuotekoodi:** TL-PA7017P KIT

Tuotteen nimi : TL-PA7017P KIT

TP-Link TL-PA7017P KIT. Tiedonsiirron enimmäisnopeus: 1000 Mbit/s, Verkkostandardit: IEEE 1901, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, Virtapistoke: Tyyppi E / F. Virrankulutus: 2,3 W, Virrankulutus valmiustilassa: 0,5 W. Tuotteen väri: Valkoinen, LED-merkkivalot: LAN, PLC, Teho, Sertifiointi: CE. Windows-käyttöjärjestelmätuki: Windows 2000, Windows 7, Windows 8, Windows 8.1, Windows Vista, Windows XP. Tuotteen leveys: 58 mm, Tuotteen syvyys: 42 mm, Tuotteen korkeus: 95 mm

Performance

Maximum data transfer rate *	1000 Mbit/s
Ethernet LAN *	✔
Ethernet LAN interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Ethernet LAN (RJ-45) ports	1
Wi-Fi *	✘
Networking standards *	IEEE 1901, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u
Power plug *	Type E / F
Built-in power socket *	✔
PowerLine standard	HomePlug AV2
Modulation	OFDM
Security algorithms	128-bit AES
Maximum operating distance	300 m
Encryption button	✔
Plug and Play	✔

Power

Power consumption (typical)	2.3 W
Power consumption (standby)	0.5 W

Design

LED indicators	LAN, PLC, Power
Product colour *	White
Certification	CE

System requirements

Windows operating systems supported	Windows 2000, Windows 7, Windows 8, Windows 8.1, Windows Vista, Windows XP

System requirements

Mac compatibility	✔
Mac operating systems supported	✔

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%

Weight & dimensions

Width	58 mm
Depth	42 mm
Height	95 mm

Certificates

Compliance certificates	RoHS

Packaging data

Package width	190 mm
Package depth	136 mm
Package height	100 mm
Package weight	580 g

Packaging content

Quantity per pack *	2 pc(s)
Quick installation guide	✔
Cables included	LAN (RJ-45)

Logistics data

Harmonized System (HS) code	85171800

System requirements

Linux operating systems supported ✔

6935364089078

0845973089078

845973089078