



## TP-Link Archer C80 langaton reititin Gigabitti Ethernet Kaksitaajuus (2,4 GHz/5 GHz) musta

**Tuotemerkki :** TP-Link

**Tuotekoodi:** ARCHER C80

**Tuotteen nimi :** Archer C80

TP-Link Archer C80. WAN -liitintyyppi: RJ-45. Wi-Fi-taajuus: Kaksitaajuus (2,4 GHz/5 GHz), Wi-Fi-standardi: Wi-Fi 5 (802.11ac), WLAN-tiedonsiirtonopeus (maks.): 1300 Mbit/s. Ethernet LAN -käyttöliittymän tyyppi: Gigabitti Ethernet, Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s, Kaapelitekniikka: 10/100/1000Base-T(X). Tietoturva-algoritmit: 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK. Tuotetyyppi: Pöytäreititin, Tuotteen väri: musta, LED-merkkivalot: LAN, Teho, Tila, WLAN, WPS



<b>WAN connection</b>		<b>Protocols</b>	
Ethernet WAN *	✓	Universal Plug and Play (UPnP)	✓
SIM card slot *	✗	<b>Design</b>	
WAN connection type	RJ-45	Product colour	Black
<b>Wireless LAN features</b>		Wall mountable	✓
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)	LED indicators	LAN, Power, Status, WLAN, WPS
Top Wi-Fi standard *	Wi-Fi 5 (802.11ac)	On/off switch	✓
WLAN data transfer rate (max) *	1300 Mbit/s	Product type *	Tabletop router
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)	<b>Packaging content</b>	
WLAN data transfer rate (first band)	1300 Mbit/s	Cables included	AC, LAN (RJ-45)
<b>Network</b>		AC adapter included	✓
Ethernet LAN *	✓	Quick installation guide	✓
Ethernet LAN interface type *	Gigabit Ethernet	<b>Antenna</b>	
Ethernet LAN data rates	10,100,1000 Mbit/s	Antenna design *	External
Cabling technology	10/100/1000Base-T(X)	Antennas quantity	4
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Detachable antenna(s)	✗
Port forwarding	✓	Transmit power	CE: <20dBm(2.4 GHz), <23dBm(5.15 GHz~5.25 GHz), FCC:<30dBm(2.4 GHz & 5 GHz)
Dynamic DNS (DDNS)	✓	<b>Power</b>	
<b>Ports &amp; interfaces</b>		Power source type *	DC
Ethernet LAN (RJ-45) ports *	5	Output voltage	12 V
USB port *	✗	<b>Operational conditions</b>	
Memory card slot(s)	✗	Operating temperature (T-T)	0 - 40 °C
DC-in jack	✓	Storage temperature (T-T)	-40 - 70 °C
<b>Management features</b>		Operating relative humidity (H-H)	10 - 90%
		Storage relative humidity (H-H)	5 - 90%

Management features		System requirements			
Reset button	✓	Browser supported	Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0		
WPS push button	✓				
Security		Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows 98SE, Windows NT, Windows Vista, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows Vista x64, Windows XP, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64		
Security algorithms	64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK				
Firewall	✓				
Guest access	✓				
Access Control List (ACL)	✓				
Stateful Packet Inspection (SPI)	✓				
MAC address filtering	✓				
DMZ support	✓				
Protocols				Linux operating systems supported	✓
DHCP client	✓			Mac operating systems supported	MacOS
DHCP server	✓	Mac compatibility	✓		
		Packaging data			
		Package width	350 mm		
		Package depth	240 mm		
		Package height	82 mm		
		Package weight	800 g		



6935364088873

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.